

Win Templeton

CONSULTING ENGINEER

DOOLY BUILDING
109 WEST SECOND SOUTH
SALT LAKE CITY 1, UTAH
TELEPHONE 9-5376

June 27, 1948.

Mr. A. L. Everson
City Clerk,
Shelley, Idaho.

Dear Mr. Everson:

Enclosed herewith are plans, specifications and list of material required for installation of a booster pump in your distribution system. Also a ~~plan~~ pamphlet dealing with tank repairs.

The pump specified will give you an operating pressure of 45 to 50 pounds which I believe will greatly improve the distribution of water with out to much danger of over taxing the old water mains.

The Fairbanks-Morse Pump, Model # 5811; size five; 8" impeller # D5C1B will meet these specifications.

The dealers inform me that the equipment and material for this installation can be delivered in 30 to 40 days.

I plan on coming to Shelley to run a test on the number two pump as soon as I receive the information on the present pump from Fairbanks-Morse.

Very truly yours,

Win Templeton
Win Templeton.

CHARACTERISTICS OF THE
 CAPACITANCE OF THE
 CAPACITOR FOR
 50 HZ. 500 V. AC. CAPACITANCE OF THE CAPACITOR
 50 HZ. 500 V. AC. CAPACITANCE OF THE CAPACITOR

AS THE POSITIVE CURRENT IN THE CAPACITOR

