

STATE OF IDAHO
DEPARTMENT OF WATER RESOURCES
WELL DRILLER'S REPORTUSE TYPEWRITER OR
BALLPOINT PENState law requires that this report be filed with the Director, Department of Water Resources
within 30 days after the completion or abandonment of the well.983
FNT'D

1. WELL OWNER

Name Donald Rower
Address Rathdrum, Idaho
Owner's Permit No. 95-80-N-8

7. WATER LEVEL

Static water level 150 feet below land surface.
Flowing? ☐ Yes ☒ No G.P.M. flow 1
Artesian closed-in pressure _____ p.s.i.
Controlled by: ☐ Valve ☐ Cap ☐ Plug
Temperature _____ °F. Quality _____

2. NATURE OF WORK

☒ New well ☐ Deepened ☐ Replacement
☐ Abandoned (describe method of abandoning) _____

8. WELL TEST DATA

☐ Pump ☐ Bailor ☒ Air ☐ Other _____

Discharge G.P.M.	Pumping Level	Hours Pumped

3. PROPOSED USE

☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal
☐ Industrial ☐ Stock ☐ Waste Disposal or Injection
☐ Other _____ (specify type)

4. METHOD DRILLED

☒ Rotary ☐ Air ☐ Hydraulic ☐ Reverse rotary
☐ Cable ☐ Dug ☐ Other _____

5. WELL CONSTRUCTION

Casing schedule: ☒ Steel ☐ Concrete ☐ Other _____

Thickness	Diameter	From	To
<u>.250</u> inches	<u>8</u> inches	<u>1</u> feet	<u>90</u> feet
<u>.250</u> inches	<u>6</u> inches	<u>1</u> feet	<u>114</u> feet
_____ inches	_____ inches	_____ feet	_____ feet
_____ inches	_____ inches	_____ feet	_____ feet

Was casing drive shoe used? ☒ Yes ☐ NoWas a packer or seal used? ☐ Yes ☒ NoPerforated? ☐ Yes ☒ NoHow perforated? ☐ Factory ☐ Knife ☐ Torch

Size of perforation _____ inches by _____ inches

Number	From	To
_____ perforations	_____ feet	_____ feet
_____ perforations	_____ feet	_____ feet
_____ perforations	_____ feet	_____ feet

Well screen installed? ☐ Yes ☒ No

Manufacturer's name _____

Type _____ Model No. _____

Diameter _____ Slot size _____ Set from _____ feet to _____ feet

Diameter _____ Slot size _____ Set from _____ feet to _____ feet

Gravel packed? ☐ Yes ☐ No ☐ Size of gravel _____

Placed from _____ feet to _____ feet

Surface seal depth _____ Material used in seal: ☐ Cement grout☐ Puddling clay ☐ Well cuttingsSealing procedure used: ☐ Slurry pit ☐ Temp. surface casing☒ Overbore to seal depthMethod of joining casing: ☐ Threaded ☒ Welded ☐ Solvent

Weld _____

☐ Cemented between strata

Describe access port _____

9. LITHOLOGIC LOG


Hole Diam.	Depth		Material	Water	
	From	To		Yes	No
<u>8</u>	<u>-</u>	<u>90</u>	<u>large gravel</u>		
	<u>90</u>	<u>101</u>	<u>granite</u>		
	<u>101</u>	<u>114</u>	<u>gravel</u>		
<u>114</u>	<u>114</u>	<u>158</u>	<u>granite</u>		
	<u>158</u>	<u>164</u>	<u>decomposed granite</u>	<u>x</u>	
	<u>164</u>	<u>300</u>	<u>granite</u>		

10.

Work started 5-11-80 finished 5-14-80

6. LOCATION OF WELL

Sketch map location must agree with written location.



Subdivision Name _____

Lot No. _____ Block No. _____

County KootenaiNE 1/4 SE 1/4 Sec. 3, T. 52 N., R. 4 E/W

11. DRILLERS CERTIFICATION

I/We certify that all minimum well construction standards were
complied with at the time the rig was removed.Firm Name FINDLAY
George Malone Drilling Firm No. 274 62Address Hayden Lake, Idaho Date 5-15-80Signed by (Firm Official) Paul E. Findlay

and

(Operator) Paul E. Findlay