

POSTED

STATE OF IDAHO
DEPARTMENT OF WATER RESOURCESUSE TYPEWRITER OR
BALLPOINT PEN

WELL DRILLER'S REPORT

State law requires that this report be filed with the Director, Department of Water Resources
within 30 days after the completion or abandonment of the well.

1. WELL OWNER

Name P. DOUGLASS OR LINDA L. SMITH
Address 1147 N. HIGH ST. COA. 10. 83814
Owner's Permit No. 95-83-N-78

7. WATER LEVEL

Static water level 100 feet below land surface.
Flowing? ☐ Yes ☒ No G.P.M. flow _____
Artesian closed-in pressure _____ p.s.i.
Controlled by: ☐ Valve ☐ Cap ☐ Plug
Temperature _____ OF. Quality _____

2. NATURE OF WORK

☒ New well ☐ Deepened ☐ Replacement
☐ Abandoned (describe method of abandoning) _____

8. WELL TEST DATA

☐ Pump ☐ Bailer ☒ Air ☐ Other _____

Discharge G.P.M.	Pumping Level	Hours Pumped
<u>25 +</u>	<u>VARIOUS</u>	<u>1</u>

3. PROPOSED USE

☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal
☐ Industrial ☐ Stock ☐ Waste Disposal or Injection
☐ Other _____ (specify type)

4. METHOD DRILLED

☒ Rotary ☐ Air ☐ Hydraulic ☐ Reverse rotary
☐ Cable ☐ Dug ☐ Other _____

5. WELL CONSTRUCTION

Casing schedule: ☒ Steel ☐ Concrete ☐ Other _____

Thickness	Diameter	From	To
<u>1.250</u> inches	<u>6</u> inches	<u>1.5</u> feet	<u>20</u> feet
_____ inches	_____ inches	_____ feet	_____ feet
_____ inches	_____ inches	_____ feet	_____ feet
_____ inches	_____ inches	_____ feet	_____ feet

Was casing drive shoe used? ☒ Yes ☐ NoWas a packer or seal used? ☐ Yes ☒ NoPerforated? ☐ Yes ☒ NoHow perforated? ☐ Factory ☐ Knife ☐ Torch

Size of perforation _____ inches by _____ inches

Number	From	To
_____ perforations	_____ feet	_____ feet
_____ perforations	_____ feet	_____ feet
_____ perforations	_____ feet	_____ feet

Well screen installed? ☐ Yes ☒ No

Manufacturer's name _____

Type _____ Model No. _____

Diameter _____ Slot size _____ Set from _____ feet to _____ feet

Diameter _____ Slot size _____ Set from _____ feet to _____ feet

Gravel packed? ☐ Yes ☒ No ☐ Size of gravel _____

Placed from _____ feet to _____ feet

Surface seal depth 20' Material used in seal: ☐ Cement grout☒ Puddling clay ☒ Well cuttingsSealing procedure used: ☐ Slurry pit ☐ Temp. surface casing☒ Overbore to seal depthMethod of joining casing: ☐ Threaded ☒ Welded ☐ Solvent

Weld _____

☐ Cemented between strata

Describe access port _____

9. LITHOLOGIC LOG

Hole Diam.	Depth		Material	Water	
	From	To		Yes	No
8	0	20	TOP SOIL & SHALE		☒
6	20	125	SOFT SHALE		☒
	125	210	MEDIUM SHALE	☒	
	210	300	HARD SHALE		☒
	300	350	HARD SHALE w/2 SOFT SEAMS		☒

LINER NECESSARY! OWNER WILL INSTALL.

LINER SHOULD BE INSTALLED

WITHIN 4 DAYS.

RECEIVED

AUG 9 1983

10.

Work started 6-21-83 finished 6-23-83

6. LOCATION OF WELL

Sketch map location must agree with _____

N
W E
S

Subdivision Name _____

Lot No. _____ Block No. _____

County KOOTENAI
NW SE 17 Sec. 17 T. 52 N. 3 R. 3 E.

11. DRILLERS CERTIFICATION

I/We certify that all minimum well construction standards were
complied with at the time the rig was removed.Firm Name ASSOCIATED WELL DRILLERS, INC. No. 245Address Box 723 - Coa. 10. Date 6-24-83Signed by (Firm Official) And _____and
(Operator) Charles Shultz