RECEIVED

REPORT OF WELL DRILLER
State of Idaho

(END)

State law requires that this report shall be filed with the State Reclamation Engineer within 30 days after completion or abandonment of the well.

WELL OWNER:
Name: Kootenai County (Airport)
Address: County Court House
Coeur d'Alene, Idaho 95-69-N-26
Owner's Permit No. 95-7215

NATURE OF WORK (check): Replacement well [ ] New well [X] Deepened [ ] Abandoned [ ]

Water is to be used for: Domestic

METHOD OF CONSTRUCTION: Rotary [ ] Cable [X] Dug [ ] Other ________ (explain)

CASING SCHEDULE: Threaded [ ] Welded [X]
10 "Diam. from 0 ft. to 328 ft.
"Diam. from ft. to ft.
"Diam. from ft. to ft.
"Diam. from ft. to ft.

Thickness of casing: 344 Material:
Steel [X] concrete [ ] wood [ ] other [ ] (explain)

PERFORATED? Yes [ ] No [X] Type of perforator used:

Size of perforations: " by "
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

WAS SCREEN INSTALLED? Yes [X] No [ ]
Manufacturer's name: Johnson OUP
Type: Stainless Steel Model No. 304
Diam. 4½ Slot size .040 Set from 328 ft. to 348 ft.
Diam. Slot size Set from ft. to ft.

CONSTRUCTION: Well gravel packed? Yes [ ] No. [X] size of gravel ________ Gravel placed from ft. to ft. Surface seal provided? Yes [X] No [ ] To what depth? 303 ft. Material used in seal: Puddling Clay

Did any strata contain unusable water? Yes [ ] No. [X] Type of water: ________ Depth of strata ________ ft. Method of sealing strata off:

Surface casing used? Yes [X] No. [ ]
Cemented in place? Yes [X] on top 24 ft. No [X] puddling clay seal

Locate well in section

Sec.

LOCATION OF WELL: County Kootenie
NE ¼ NE ¼ Sec. 15 T. 51 N/S R. 4 E/W

Size of drilled hole: 10 in. ID Total depth of well: 348 Standing water level below ground: 303 Temp. ____ Fahr. ° Test delivery: ________ gpm or ________ cfs Pump? [ ] Bail [ ]

Size of pump and motor used to make test: To pump 200 GPM (Estimated)

Length of time of test: ____ Hrs. ____ Min.

Drawdown: ____ ft. Artesian pressure: ft. above land surface ____ Give flow ____ cfs or ____ gpm. Shutoff pressure: ________

Controlled by: Valve [ ] Cap [ ] Plug [ ] No control [ ] Does well leak around casing? Yes [ ] No [X]

DEPTH FROM (FEET)	DEPTH TO (FEET)	MATERIAL	WATER YES OR NO
0	3	Top soil	no
3	20	Large gravel & Boulders	no
20	65	Sand & silt	no
65	68	One big boulder	no
68	200	Pea gravel with lots of light grey silt	no
200	213	sand & silt	no
213	220	Cobble stones	no
220	260	Very tight silt with sand and small gravel	no
260	294	silt and pea gravel	no
294	303	coarse sand & very tight heavy silt	no
303		Water	
303	308	Very fine, clean, washed sand	yes
308	315	Coarse washed sand with a small amount of pea gravel	yes
315	320	Fine sand	yes
320	348	Coarse washed sand	yes

Work started: May 14 - 1968
Work finished: July 10 - 1968

Well Driller's Statement: This well was drilled under my supervision and this report is true to the best of my knowledge.

Name: [signature]
Address: [illegible]
Signed by: [signature]
License No. 105 Date: July 10 - 1968

Use other side for additional remarks

CNA

USGS