RECEIVED
Form 238-7
3/95
AUG 2 2 1997

IDAHO DEPARTMENT OF WATER RESOURCES
WELL DRILLER'S REPORT

Use Typewriter or Ballpoint Pen

Office Use Only
Inspected by TDK
Twp____ Rge____ Sec____
____1/4 ____1/4 ____1/4
Lat: : : Long: : :

NORTHERN REGION
1. DRILLING PERMIT NO. 95-97-N-80 - 097108
Other IDWR No. D0003937

2. OWNER:
Name EARL REAMY
Address 3001 E. SELTICE
City POST FALLS State ID Zip 83854

3. LOCATION OF WELL by legal description:
Sketch map location must agree with written location.

N / W / E / S

Twp 51N North ☒ or South ☐
Rge 4W East ☐ or West ☒
Sec 20, NW 1/4 (10 acres) SW 1/4 (40 acres) ____ 1/4 (160 acres)
Gov't Lot ____ County Kootenai
Lat: : : Long: : :
Address of Well Site MYERS RD
City
(Give at least name of road + Distance to Road or Landmark)
Lt.____ Blk.____ Sub. Name____

4. USE:
☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation
☐ Thermal ☐ Injection ☐ Other____

5. TYPE OF WORK check all that apply (Replacement etc.)
☒ New Well ☐ Modify ☐ Abandonment ☐ Other____

6. DRILL METHOD
☒ Air Rotary ☐ Cable ☐ Mud Rotary ☐ Other____

7. SEALING PROCEDURES

SEAL/FILTER PACK Material	From	To	AMOUNT Sacks or Pounds	METHOD
Bentonite	0	15	10 sacks	pour in

Was drive shoe used? ☐ Y ☒ N Shoe Depth(s)____
Was drive shoe seal tested? ☐ Y ☒ N How?____

8. CASING/LINER:

Diameter	From	To	Gauge	Material	Casing	Liner	Welded	Threaded
6"	+2	295	.322	Steel	☒	☐	☒	☐
					☐	☐	☐	☐
					☐	☐	☐	☐

Length of Headpipe____ Length of Tailpipe____

9. PERFORATIONS/SCREENS
☒ Perforations Method Air perforator
☐ Screens Screen Type____

From	To	Slot Size	Number	Diameter	Material	Casing	Liner
295'	295'	1"	280		Steel	☒	☐
						☐	☐
						☐	☐

10. STATIC WATER LEVEL OR ARTESIAN PRESSURE:
237 ft. below ground 237 Artesian pressure ____ lb.
Depth flow encountered Steel Cap welded ft. Describe access port or control devices:

11. WELL TESTS:
☐ Pump ☐ Bailer ☒ Air ☐ Flowing Artesian

Yield gal./min.	Drawdown	Pumping Level	Time
flooded	zero		
30+	100%	295'	1 hr.

Water Temp. cold Bottom hole temp. cold
Water Quality test or comments: cool, clear, no smell
Depth first Water Encountered 237

12. LITHOLOGIC LOG: (Describe repairs or abandonment)

Bore Dia.	From	To	Remarks: Lithology, Water Quality & Temperature	Water Y	Water N
8"	0	6	Topsoil		X
8"	6	90	Sand & gravel - 3/4 minus		X
8"	90	99	Sand & gravel - cobbles		X
8"	99	115	Sand & gravel - 3/4 minus		X
8"	115	237	Sand & gravel - fine		X
6"	237	267	Sand & gravel - 3/4 minus	X	
6"	267	279	Sand - fine - gray	X	
6"	279	295	Sand & gravel - 3/4 minus	X	

Completed Depth 295 (Measurable)
Date: Started 8/01/97 Completed 8/02/97

13. DRILLER'S CERTIFICATION
I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Firm Name United Drilling Inc. Firm No. 414
Firm Official [signature] Date 8/13/97
and
Supervisor or Operator Jason C. Beckham Date 8/13/97
(Sign once if Firm Official & Operator)

NWSW 20 51N 4W

WHITE COPY TO WATER RESOURCES