



WELL DRILLER'S REPORT

State law requires that this report be filed with the Director, Department of Water Resources
within 30 days after the completion or abandonment of the well.

RECEIVED

1. WELL OWNER Name <u>Murray Danzig</u> Address <u>E. 4014 Sprague, Spokane, WA 99202</u> Owner's Permit No. <u>95-80-N-45</u>		7. WATER LEVEL NOV 18 1980 Static water level <u>100</u> feet below land surface Flowing? ☐ Yes ☒ No Artesian closed-in pressure _____ p.s.i. Controlled by: ☐ Valve ☐ Cap ☐ Plug Temperature _____ °F. Quality _____																																																					
2. NATURE OF WORK ☒ New well ☐ Deepened ☐ Replacement ☐ Abandoned (describe method of abandoning) _____		8. WELL TEST DATA ☐ Pump ☐ Bailer ☒ Air ☐ Other _____ Discharge G.P.M. <u>8-10 gpm</u> Pumping Level _____ Hours Pumped _____ Est. Airlift _____																																																					
3. PROPOSED USE ☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal ☐ Industrial ☐ Stock ☐ Waste Disposal or Injection ☐ Other _____ (specify type)		9. LITHOLOGIC LOG <table border="1"><thead><tr><th rowspan="2">Hole Diam.</th><th colspan="2">Depth</th><th rowspan="2">Material</th><th colspan="2">Water</th></tr><tr><th>From</th><th>To</th><th>Yes</th><th>No</th></tr></thead><tbody><tr><td>6</td><td>0</td><td>78</td><td>Basalt</td><td></td><td>X</td></tr><tr><td>6</td><td>78</td><td>150</td><td>Clay, Gray</td><td></td><td>X</td></tr><tr><td>6</td><td>150</td><td>198</td><td>Basalt, Black</td><td>X</td><td></td></tr><tr><td>6</td><td>198</td><td>230</td><td>Basalt, Black</td><td></td><td>X</td></tr><tr><td>6</td><td>230</td><td>240</td><td>Basalt, Black</td><td>X</td><td></td></tr><tr><td>6</td><td>240</td><td>270</td><td>Clay, Gray</td><td></td><td>X</td></tr><tr><td>6</td><td>270</td><td>280</td><td>Sandy Clay</td><td></td><td>X</td></tr></tbody></table>		Hole Diam.	Depth		Material	Water		From	To	Yes	No	6	0	78	Basalt		X	6	78	150	Clay, Gray		X	6	150	198	Basalt, Black	X		6	198	230	Basalt, Black		X	6	230	240	Basalt, Black	X		6	240	270	Clay, Gray		X	6	270	280	Sandy Clay		X
Hole Diam.	Depth		Material		Water																																																		
	From	To		Yes	No																																																		
6	0	78	Basalt		X																																																		
6	78	150	Clay, Gray		X																																																		
6	150	198	Basalt, Black	X																																																			
6	198	230	Basalt, Black		X																																																		
6	230	240	Basalt, Black	X																																																			
6	240	270	Clay, Gray		X																																																		
6	270	280	Sandy Clay		X																																																		
4. METHOD DRILLED ☒ Rotary ☐ Air ☐ Hydraulic ☐ Reverse rotary ☐ Cable ☐ Dug ☐ Other _____		10. Work started <u>10/30/80</u> finished <u>11/03/80</u>																																																					
5. WELL CONSTRUCTION Casing schedule: ☒ Steel ☐ Concrete ☐ Other _____ <table border="1"><thead><tr><th>Thickness</th><th>Diameter</th><th>From</th><th>To</th></tr></thead><tbody><tr><td><u>.250</u> inches</td><td><u>6</u> inches</td><td><u>1 1/2</u> feet</td><td><u>88 1/2</u> feet</td></tr><tr><td>_____ inches</td><td>_____ inches</td><td>_____ feet</td><td>_____ feet</td></tr><tr><td>_____ inches</td><td>_____ inches</td><td>_____ feet</td><td>_____ feet</td></tr><tr><td>_____ inches</td><td>_____ inches</td><td>_____ feet</td><td>_____ feet</td></tr></tbody></table> Was casing drive shoe used? ☒ Yes ☐ No Was a packer or seal used? ☐ Yes ☒ No Perforated? ☐ Yes ☒ No How perforated? ☐ Factory ☐ Knife ☐ Torch Size of perforation _____ inches by _____ inches Number _____ From _____ To _____ _____ perforations _____ feet _____ feet _____ perforations _____ feet _____ feet _____ perforations _____ feet _____ feet Well screen installed? ☐ Yes ☒ No Manufacturer's name _____ Type _____ Model No. _____ Diameter _____ Slot size _____ Set from _____ feet to _____ feet Diameter _____ Slot size _____ Set from _____ feet to _____ feet Gravel packed? ☐ Yes ☒ No ☐ Size of gravel _____ Placed from _____ feet to _____ feet Surface seal depth <u>80'</u> Material used in seal: ☐ Cement grout ☒ Puddling clay ☐ Well cuttings Sealing procedure used: ☐ Slurry pit ☐ Temp. surface casing ☒ Overbore to seal depth Method of joining casing: ☐ Threaded ☒ Welded ☐ Solvent Weld ☐ Cemented between strata Describe access port _____		Thickness	Diameter	From	To	<u>.250</u> inches	<u>6</u> inches	<u>1 1/2</u> feet	<u>88 1/2</u> feet	_____ inches	_____ inches	_____ feet	_____ feet	_____ inches	_____ inches	_____ feet	_____ feet	_____ inches	_____ inches	_____ feet	_____ feet	11. DRILLERS CERTIFICATION I/We certify that all minimum well construction standards were complied with at the time the rig was removed. Ponderosa Drilling Firm Name <u>& Development, Inc.</u> Firm No. <u>228</u> Address <u>Spokane, WA 99206</u> Date <u>11/10/80</u> Signed by (Firm Official) <u>W. Scott Barratt</u> and <u>Paul Hawkins</u> (Operator)																																	
Thickness	Diameter	From	To																																																				
<u>.250</u> inches	<u>6</u> inches	<u>1 1/2</u> feet	<u>88 1/2</u> feet																																																				
_____ inches	_____ inches	_____ feet	_____ feet																																																				
_____ inches	_____ inches	_____ feet	_____ feet																																																				
_____ inches	_____ inches	_____ feet	_____ feet																																																				
6. LOCATION OF WELL Sketch map location must agree with well location. Subdivision Name _____ Lot No. <u>2</u> Block No. _____ County <u>Kootenai</u> Sec. <u>35</u> T. <u>50</u> N. R. <u>4W</u> E.W. USE ADDITIONAL SHEETS IF NECESSARY - FORWARD THE WHITE COPY TO THE DEPARTMENT																																																							

