


WELL MILLER'S REPORT

State law requires that this report be filed with the Director, Department of Water Resources
within 30 days after the completion or abandonment of the well.

1. WELL OWNER Name <u>John C. or Verda C. Mallon</u> Address <u>563 Capitol Dr. Bencia Calif 94510</u> Owner's Permit No. <u>95-80-N-48</u>	7. WATER LEVEL Static water level <u>135</u> feet below land surface. Flowing? ☐ Yes ☒ No G.P.M. flow _____ Artesian closed in pressure _____ p.s.i. Controlled by: ☐ Valve ☐ Cap ☐ Plug Temperature _____ of. Quality <u>good</u> <i>Describe artesian or temperature zones below</i>																																														
2. NATURE OF WORK ☒ New well ☐ Deepened ☐ Replacement ☐ Abandoned (describe abandonment procedures such as materials, plug depths, etc. in lithologic log)	8. WELL TEST DATA ☐ Pump ☐ Bailer ☒ Air ☐ Other _____ <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Discharge G.P.M.</th> <th>Pumping Level</th> <th>Hours Pumped</th> </tr> <tr> <td><u>4 1/2 to 5 gpm</u></td> <td><u>750</u></td> <td><u>1hr</u></td> </tr> </table>	Discharge G.P.M.	Pumping Level	Hours Pumped	<u>4 1/2 to 5 gpm</u>	<u>750</u>	<u>1hr</u>																																								
Discharge G.P.M.	Pumping Level	Hours Pumped																																													
<u>4 1/2 to 5 gpm</u>	<u>750</u>	<u>1hr</u>																																													
3. PROPOSED USE ☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal ☐ Industrial ☐ Stock ☐ Waste Disposal or Injection ☐ Other _____ (specify type)	9. LITHOLOGIC LOG <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Bore Diam.</th> <th colspan="2">Depth</th> <th rowspan="2">Material</th> <th colspan="2">Water</th> </tr> <tr> <th>From</th> <th>To</th> <th>Yes</th> <th>No</th> </tr> </thead> <tbody> <tr> <td>8</td> <td>0</td> <td>20</td> <td>hard granite</td> <td></td> <td>X</td> </tr> <tr> <td>6</td> <td>20</td> <td>94</td> <td>decompose granite</td> <td></td> <td>X</td> </tr> <tr> <td>6</td> <td>94</td> <td>135</td> <td>black & white granite</td> <td></td> <td>X</td> </tr> <tr> <td>6</td> <td>135</td> <td>160</td> <td>soft granite</td> <td>X</td> <td></td> </tr> <tr> <td>6</td> <td>160</td> <td>250</td> <td>soft decompose granite</td> <td></td> <td>X</td> </tr> <tr> <td>6</td> <td>250</td> <td>750</td> <td>hard black & white granite</td> <td>X</td> <td></td> </tr> </tbody> </table> 1 gpm at 145 3 1/2 to 4 at 710	Bore Diam.	Depth		Material	Water		From	To	Yes	No	8	0	20	hard granite		X	6	20	94	decompose granite		X	6	94	135	black & white granite		X	6	135	160	soft granite	X		6	160	250	soft decompose granite		X	6	250	750	hard black & white granite	X	
Bore Diam.	Depth		Material	Water																																											
	From	To		Yes	No																																										
8	0	20	hard granite		X																																										
6	20	94	decompose granite		X																																										
6	94	135	black & white granite		X																																										
6	135	160	soft granite	X																																											
6	160	250	soft decompose granite		X																																										
6	250	750	hard black & white granite	X																																											
4. METHOD DRILLED ☒ Rotary ☒ Air ☐ Hydraulic ☐ Reverse rotary ☐ Cable ☐ Dug ☐ Other _____	RECEIVED JUL 1988 Department of Water Resources Northern District Office																																														
5. WELL CONSTRUCTION Casing schedule: ☒ Steel ☐ Concrete ☐ Other _____ <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Thickness</th> <th>Diameter</th> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr> <td>250 inches</td> <td>6 inches</td> <td>1 feet</td> <td>20 feet</td> </tr> <tr> <td>160 inches</td> <td>4 inches</td> <td>15 feet</td> <td>750 feet</td> </tr> </tbody> </table> Was casing drive shoe used? ☒ Yes ☐ No Was a packer or seal used? ☒ Yes ☐ No Perforated? ☒ drill ☒ Yes ☐ No How perforated? ☐ Factory ☐ Knife ☐ Torch Size of perforation <u>1/2</u> inches by <u>1/2</u> inches <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Number</th> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr> <td>150 perforations</td> <td>250 feet</td> <td>500 feet</td> </tr> <tr> <td>250 perforations</td> <td>650 feet</td> <td>750 feet</td> </tr> </tbody> </table> Well screen installed? ☐ Yes ☒ No Manufacturer's name _____ Type _____ Model No. _____ Diameter _____ Slot size _____ Set from _____ feet to _____ feet Diameter _____ Slot size _____ Set from _____ feet to _____ feet Gravel packed? ☐ Yes ☒ No ☐ Size of gravel _____ Placed from _____ feet to _____ feet Surface seal depth <u>20</u> Material used in seal: ☐ Cement grout ☒ Bentonite ☐ Puddling clay ☐ Sealing procedure used: ☐ Slurry pit ☐ Temp. surface casing ☒ Overbore to seal depth Method of joining casing: ☐ Threaded ☒ Welded ☐ Solvent Weld ☐ Cemented between strata Describe access port _____		Thickness	Diameter	From	To	250 inches	6 inches	1 feet	20 feet	160 inches	4 inches	15 feet	750 feet	Number	From	To	150 perforations	250 feet	500 feet	250 perforations	650 feet	750 feet																									
Thickness	Diameter	From	To																																												
250 inches	6 inches	1 feet	20 feet																																												
160 inches	4 inches	15 feet	750 feet																																												
Number	From	To																																													
150 perforations	250 feet	500 feet																																													
250 perforations	650 feet	750 feet																																													
6. LOCATION OF WELL Sketch map location must agree with written location.  Subdivision Name _____ Lot No. _____ Block No. _____ County <u>Kootenai</u> SE 1/4 SE 1/4 Sec 6 T 51 N 1/2 R 5 4th	10. Work started <u>6/29/88</u> finished <u>6/31/88</u>																																														
11. DRILLERS CERTIFICATION I/We certify that all minimum well construction standards were complied with at the time the rig was removed. Firm Name <u>Associated Drilling, Inc.</u> Firm No. <u>245</u> Address <u>P.O. Box 819</u> Date <u>7/5/88</u> <u>Coeur d'Alene, ID</u> Signed by (Firm Official) <u>Ed R. Volking</u> and (Operator) <u>Tim Volking</u>	BERG																																														

BERG

- [Home](#)
- [Idaho.gov](#)
- [Contact Us](#)

Department of Water Resources



Map Tools

Display Layers
☒ ESPA

Map Background
☐ No Background
☐ USGS Quadrangle
☒ Aerial Photo

Legend [\(Show\)](#)

May Need To Zoom In To See ESPA Cells

Search By Address

Address

City

[Find Address](#)

Search By Parcel Number

PIN

County

If a county is missing from the list then we do not have its parcel information
[Find PIN](#)

Search By PLSS

Township

☐ North
☐ South
Range

☒ East ☐ West
Section

Quarter-Quarter

[Find Township](#)

- [Home](#)
- [Disclaimer](#)
- [About PDF Files](#)
- [Accessibility](#)
- [Privacy & Security](#)
- [Contact Us](#)
- [Idaho.gov](#)

BERG