

4840 cy

GOECKNER PIN 50N05W-10-4830

WELL



50N05W-10-4830

4840 cl

HOUSE

50N05W-10-4850

WELL DRILLER'S REPORT

State law requires that this report be filed with the Director, Department of Water Resources within 30 days after the completion or abandonment of the well.

1. WELL OWNER Name <u>RONALD JANAS</u> Address <u>51080 PENNY LANE</u> Owner's No. <u>POST FALLS WA 83854</u>	7. WATER LEVEL Static water level <u>46</u> feet below land surface. Flowing? ☐ Yes ☒ No G.P.M. flow _____ Artesian closed-in pressure _____ p.s.i. Controlled by: ☐ Valve ☐ Cap ☐ Plug Temperature _____ °F. Quality _____ Describe artesian or temperature zones below.																																																																																							
2. NATURE OF WORK <u>95-86-N-37</u> ☒ New well ☐ Deepened ☐ Replacement ☐ Abandoned (describe abandonment procedures such as materials, plug depths, etc. in lithologic log)	8. WELL TEST DATA ☐ Pump ☐ Bailor ☒ Air ☐ Other _____ <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>Discharge G.P.M.</th> <th>Pumping Level</th> <th>Hours Pumped</th> </tr> <tr> <td><u>116 gpm</u></td> <td><u>300</u></td> <td><u>2 HRS</u></td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </table>	Discharge G.P.M.	Pumping Level	Hours Pumped	<u>116 gpm</u>	<u>300</u>	<u>2 HRS</u>																																																																																	
Discharge G.P.M.	Pumping Level	Hours Pumped																																																																																						
<u>116 gpm</u>	<u>300</u>	<u>2 HRS</u>																																																																																						
3. PROPOSED USE ☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal ☐ Industrial ☐ Stock ☐ Waste Disposal or Injection ☐ Other _____ (specify type)	9. LITHOLOGIC LOG <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Bore Diam.</th> <th colspan="2">Depth</th> <th rowspan="2">Material</th> <th rowspan="2">Water Yes No</th> </tr> <tr> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr> <td><u>6</u></td> <td><u>0</u></td> <td><u>1</u></td> <td><u>TOP SOIL</u></td> <td><u>X</u></td> </tr> <tr> <td><u>1</u></td> <td><u>33</u></td> <td><u>36</u></td> <td><u>GRAVEL & CLAY WITH BOULERS</u></td> <td><u>X</u></td> </tr> <tr> <td><u>33</u></td> <td><u>36</u></td> <td><u>61</u></td> <td><u>FEA GRAVEL</u></td> <td><u>X</u></td> </tr> <tr> <td><u>36</u></td> <td><u>61</u></td> <td><u>65</u></td> <td><u>SOFT GRANITE - GRAY</u></td> <td><u>X</u></td> </tr> <tr> <td><u>61</u></td> <td><u>65</u></td> <td><u>69</u></td> <td><u>" " "</u></td> <td><u>X</u></td> </tr> <tr> <td><u>65</u></td> <td><u>69</u></td> <td><u>73</u></td> <td><u>MICA SAND</u></td> <td><u>X</u></td> </tr> <tr> <td><u>69</u></td> <td><u>73</u></td> <td><u>75</u></td> <td><u>SOFT GRANITE GRAY 1.56 gpm</u></td> <td><u>X</u></td> </tr> <tr> <td><u>75</u></td> <td><u>116</u></td> <td><u>131</u></td> <td><u>" " "</u></td> <td><u>X</u></td> </tr> <tr> <td><u>116</u></td> <td><u>131</u></td> <td><u>141</u></td> <td><u>FIRM " "</u></td> <td><u>X</u></td> </tr> <tr> <td><u>131</u></td> <td><u>141</u></td> <td><u>222</u></td> <td><u>BROKEN " " 6 Gpm</u></td> <td><u>X</u></td> </tr> <tr> <td><u>141</u></td> <td><u>222</u></td> <td><u>246</u></td> <td><u>FIRM " "</u></td> <td><u>X</u></td> </tr> <tr> <td><u>222</u></td> <td><u>246</u></td> <td><u>254</u></td> <td><u>" " MIXED COICES</u></td> <td><u>X</u></td> </tr> <tr> <td><u>246</u></td> <td><u>254</u></td> <td><u>282</u></td> <td><u>" " GRAY-SEAMS 2 Gpm</u></td> <td><u>X</u></td> </tr> <tr> <td><u>254</u></td> <td><u>282</u></td> <td><u>295</u></td> <td><u>HARD " BLACK-WHITE</u></td> <td><u>X</u></td> </tr> <tr> <td><u>282</u></td> <td><u>295</u></td> <td><u>302</u></td> <td><u>SOFT " GREEN 2 Gpm</u></td> <td><u>X</u></td> </tr> <tr> <td><u>295</u></td> <td><u>302</u></td> <td></td> <td><u>FIRM " GRAY</u></td> <td><u>X</u></td> </tr> </tbody> </table>	Bore Diam.	Depth		Material	Water Yes No	From	To	<u>6</u>	<u>0</u>	<u>1</u>	<u>TOP SOIL</u>	<u>X</u>	<u>1</u>	<u>33</u>	<u>36</u>	<u>GRAVEL & CLAY WITH BOULERS</u>	<u>X</u>	<u>33</u>	<u>36</u>	<u>61</u>	<u>FEA GRAVEL</u>	<u>X</u>	<u>36</u>	<u>61</u>	<u>65</u>	<u>SOFT GRANITE - GRAY</u>	<u>X</u>	<u>61</u>	<u>65</u>	<u>69</u>	<u>" " "</u>	<u>X</u>	<u>65</u>	<u>69</u>	<u>73</u>	<u>MICA SAND</u>	<u>X</u>	<u>69</u>	<u>73</u>	<u>75</u>	<u>SOFT GRANITE GRAY 1.56 gpm</u>	<u>X</u>	<u>75</u>	<u>116</u>	<u>131</u>	<u>" " "</u>	<u>X</u>	<u>116</u>	<u>131</u>	<u>141</u>	<u>FIRM " "</u>	<u>X</u>	<u>131</u>	<u>141</u>	<u>222</u>	<u>BROKEN " " 6 Gpm</u>	<u>X</u>	<u>141</u>	<u>222</u>	<u>246</u>	<u>FIRM " "</u>	<u>X</u>	<u>222</u>	<u>246</u>	<u>254</u>	<u>" " MIXED COICES</u>	<u>X</u>	<u>246</u>	<u>254</u>	<u>282</u>	<u>" " GRAY-SEAMS 2 Gpm</u>	<u>X</u>	<u>254</u>	<u>282</u>	<u>295</u>	<u>HARD " BLACK-WHITE</u>	<u>X</u>	<u>282</u>	<u>295</u>	<u>302</u>	<u>SOFT " GREEN 2 Gpm</u>	<u>X</u>	<u>295</u>	<u>302</u>		<u>FIRM " GRAY</u>	<u>X</u>
Bore Diam.	Depth		Material	Water Yes No																																																																																				
	From	To																																																																																						
<u>6</u>	<u>0</u>	<u>1</u>	<u>TOP SOIL</u>	<u>X</u>																																																																																				
<u>1</u>	<u>33</u>	<u>36</u>	<u>GRAVEL & CLAY WITH BOULERS</u>	<u>X</u>																																																																																				
<u>33</u>	<u>36</u>	<u>61</u>	<u>FEA GRAVEL</u>	<u>X</u>																																																																																				
<u>36</u>	<u>61</u>	<u>65</u>	<u>SOFT GRANITE - GRAY</u>	<u>X</u>																																																																																				
<u>61</u>	<u>65</u>	<u>69</u>	<u>" " "</u>	<u>X</u>																																																																																				
<u>65</u>	<u>69</u>	<u>73</u>	<u>MICA SAND</u>	<u>X</u>																																																																																				
<u>69</u>	<u>73</u>	<u>75</u>	<u>SOFT GRANITE GRAY 1.56 gpm</u>	<u>X</u>																																																																																				
<u>75</u>	<u>116</u>	<u>131</u>	<u>" " "</u>	<u>X</u>																																																																																				
<u>116</u>	<u>131</u>	<u>141</u>	<u>FIRM " "</u>	<u>X</u>																																																																																				
<u>131</u>	<u>141</u>	<u>222</u>	<u>BROKEN " " 6 Gpm</u>	<u>X</u>																																																																																				
<u>141</u>	<u>222</u>	<u>246</u>	<u>FIRM " "</u>	<u>X</u>																																																																																				
<u>222</u>	<u>246</u>	<u>254</u>	<u>" " MIXED COICES</u>	<u>X</u>																																																																																				
<u>246</u>	<u>254</u>	<u>282</u>	<u>" " GRAY-SEAMS 2 Gpm</u>	<u>X</u>																																																																																				
<u>254</u>	<u>282</u>	<u>295</u>	<u>HARD " BLACK-WHITE</u>	<u>X</u>																																																																																				
<u>282</u>	<u>295</u>	<u>302</u>	<u>SOFT " GREEN 2 Gpm</u>	<u>X</u>																																																																																				
<u>295</u>	<u>302</u>		<u>FIRM " GRAY</u>	<u>X</u>																																																																																				
4. METHOD DRILLED ☒ Rotary ☐ Air ☐ Hydraulic ☐ Reverse rotary ☐ Cable ☐ Dug ☐ Other _____	10. WORK STARTED Work started <u>3-24-86</u> finished <u>4-4-86</u>																																																																																							
5. WELL CONSTRUCTION Casing schedule: ☐ Steel ☐ Concrete ☐ Other _____ <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Thickness</th> <th>Diameter</th> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr> <td><u>250</u> inches</td> <td><u>6</u> inches</td> <td><u>1</u> feet</td> <td><u>77</u> feet</td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table> Was casing drive shoe used? ☒ Yes ☐ No Was a packer or seal used? ☐ Yes ☒ No Perforated? ☐ Yes ☒ No How perforated? ☐ Factory ☐ Knife ☐ Torch Size of perforation _____ inches by _____ inches <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Number</th> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table> Well screen installed? ☐ Yes ☒ No Manufacturer's name _____ Type _____ Model No. _____ Diameter _____ Slot size _____ Set from _____ feet to _____ feet Diameter _____ Slot size _____ Set from _____ feet to _____ feet Gravel packed? ☐ Yes ☒ No ☐ Size of gravel _____ Placed from _____ feet to _____ feet Surface seal depth <u>33</u> Material used in seal: ☐ Cement grout ☒ Bentonite ☐ Puddling clay ☐ _____ Sealing procedure used: ☐ Slurry pit ☐ Temp. surface casing ☒ Overbore to seal depth Method of joining casing: ☐ Threaded ☒ Welded ☐ Solvent Weld ☐ Cemented between strata Describe access port _____	Thickness	Diameter	From	To	<u>250</u> inches	<u>6</u> inches	<u>1</u> feet	<u>77</u> feet													Number	From	To										11. DRILLERS CERTIFICATION I/We certify that all minimum well construction standards were complied with at the time the rig was removed. Firm Name <u>BRAND X.W.W.</u> Firm No. <u>789</u> Address <u>RATHDRUM WA</u> Date <u>4-17-86</u> Signed by (Firm Official) <u>Lindon Carlson</u> and _____ (Operator) <u>" "</u>																																																							
Thickness	Diameter	From	To																																																																																					
<u>250</u> inches	<u>6</u> inches	<u>1</u> feet	<u>77</u> feet																																																																																					
Number	From	To																																																																																						
6. LOCATION OF WELL Sketch map location must agree with written location. Subdivision Name _____ Lot No. _____ Block No. _____ County _____ <u>NE 1/4 SW 1/4 Sec. 10, T. 50 N., R. 5 W.</u>	RECEIVED MAY 1 1986 Department of Water Resources Northern District Office																																																																																							

USE ADDITIONAL SHEETS IF NECESSARY — FORWARD THE WHITE COPY TO THE DEPARTMENT

RECEIVED

JUN 9 1987

KOOTENAI COUNTY
ASSESSOR

AFFIDAVIT OF OWNER-OCCUPIED
PRIMARY RESIDENCE

Single Family Dwelling

☐

Multi-Family Dwelling

☐

Apartment or Condominium

☐

Mobile Home

☐

(Do you own your own land ☐ Yes ☐ No)

*(If YES, do you have a detached garage ☐ Yes ☐ No)

Commercial Improvement with Living Quarters

☐

6/9/87

Date of Application

Chris & Martha Goettker

Name of Owner (print last name first)

Telephone Number

125751

50N 05W-10-4840

Parcel Number

S 1190 Penny Lane

Mailing Address

Post Falls, ID 83854

City

State

Zip

LEGAL DESCRIPTION:

Subdivision Name

Lot

Block

LEGAL DESCRIPTION:

10

Section

50N

Township

5W

Range

I AM THE OWNER, OR AM PURCHASING, AND OCCUPY AS MY PRIMARY DWELLING THE RESIDENTIAL IMPROVEMENT AS DESCRIBED ABOVE AND HEREBY GRANT PERMISSION TO ANY GOVERNMENT AGENCY AND/OR CONTRACTOR TO CONFIRM MY STATUS RELATIVE TO IDAHO STATE RESIDENCY, AND TO RELEASE, TO THE KOOTENAI COUNTY ASSESSOR WHATEVER INFORMATION IS NECESSARY TO DO SO.

X Martha L. Goettker

Signature of Owner

**PLEASE COMPLETE AND RETURN TO KOOTENAI COUNTY ASSESSORS OFFICE **
KOOTENAI COUNTY COURTHOUSE