

STATE OF IDAHO
DEPARTMENT OF WATER RESOURCES
WELL DRILLER'S REPORTRECEIVED
NOV 24 1989
USE TYPEWRITER OR
BALLPOINT PENState law requires that this report be filed with the Director, Department of Water Resources
within 30 days after the completion or abandonment of the well.

1. WELL OWNER Name <u>Jim Dorsay</u> Address <u>W. 5123 Houston Ave. Sparrow, WA. 99208</u> Owner's Permit No. <u>95-89-N-87</u>		7. WATER LEVEL Static water level <u>400</u> feet below land surface. Flowing? ☐ Yes ☒ No G.P.M. flow _____ Artesian closed-in pressure _____ p.s.i. Controlled by: ☐ Valve ☐ Cap ☐ Plug Temperature <u>50</u> °F. Quality <u>Good</u> Describe artesian or temperature zones below.																																																																																																																	
2. NATURE OF WORK ☒ New well ☐ Deepened ☐ Replacement ☐ Abandoned (describe abandonment procedures such as materials, plug depths, etc. in lithologic log)		8. WELL TEST DATA ☐ Pump ☐ Bailor ☒ Air ☐ Other _____ <table border="1"><thead><tr><th>Discharge G.P.M.</th><th>Pumping Level</th><th>Hours Pumped</th></tr></thead><tbody><tr><td><u>20-50 GPM</u></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr></tbody></table>		Discharge G.P.M.	Pumping Level	Hours Pumped	<u>20-50 GPM</u>																																																																																																												
Discharge G.P.M.	Pumping Level	Hours Pumped																																																																																																																	
<u>20-50 GPM</u>																																																																																																																			
3. PROPOSED USE ☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal ☐ Industrial ☐ Stock ☐ Waste Disposal or Injection ☐ Other _____ (specify type)		9. LITHOLOGIC LOG <table border="1"><thead><tr><th rowspan="2">Bore Diam.</th><th colspan="2">Depth</th><th rowspan="2">Material</th><th colspan="2">Water</th></tr><tr><th>From</th><th>To</th><th>Yes</th><th>No</th></tr></thead><tbody><tr><td>10</td><td>0</td><td>1</td><td>TOP SOIL</td><td></td><td>X</td></tr><tr><td>10</td><td>1</td><td>5</td><td>BROWN CLAY - CRACKS</td><td></td><td>X</td></tr><tr><td>10 1/8</td><td>5</td><td>75</td><td>BASALT - HARD, FRAGS.</td><td></td><td>X</td></tr><tr><td>1</td><td>75</td><td>150</td><td>TAN CLAY - FIRM</td><td></td><td>X</td></tr><tr><td>1</td><td>150</td><td>190</td><td>LT. BROWN CLAY - FIRM w/ Voids</td><td></td><td>X</td></tr><tr><td>1</td><td>190</td><td>220</td><td>UPPER Dk. Bk. Sediment - FIRM</td><td></td><td>X</td></tr><tr><td>8 1/8</td><td>220</td><td>300</td><td>BASALT - HARD, FRAGS.</td><td></td><td>X</td></tr><tr><td>8</td><td>300</td><td>358</td><td>BASALT - VERY HARD</td><td></td><td>X</td></tr><tr><td>8</td><td>358</td><td>362</td><td>BASALT - FRAGS.</td><td></td><td>X</td></tr><tr><td>8</td><td>362</td><td>370</td><td>BROWN CLAY - FIRM</td><td></td><td>X</td></tr><tr><td>8</td><td>370</td><td>378</td><td>TAN CLAY - "</td><td></td><td>X</td></tr><tr><td>8</td><td>378</td><td>380</td><td>BROWN CLAY - "</td><td></td><td>X</td></tr><tr><td>8</td><td>380</td><td>425</td><td>BASALT - MED. FRAGS., 2 GPM K</td><td></td><td>X</td></tr><tr><td>8</td><td>425</td><td>465</td><td>TAN CLAY - FIRM</td><td></td><td>X</td></tr><tr><td>8</td><td>465</td><td>470</td><td>BROWN CLAY - "</td><td></td><td>X</td></tr><tr><td>8</td><td>470</td><td>490</td><td>BASALT - MED. FRAGS.</td><td></td><td>X</td></tr><tr><td>8</td><td>490</td><td>500</td><td>20-50 GPM BASALT - HARD</td><td></td><td>X</td></tr></tbody></table> WELL IS LINED w/ 4" PVC SUGGEST TEST PUMP TO ACTER MIN & EXACT YIELD		Bore Diam.	Depth		Material	Water		From	To	Yes	No	10	0	1	TOP SOIL		X	10	1	5	BROWN CLAY - CRACKS		X	10 1/8	5	75	BASALT - HARD, FRAGS.		X	1	75	150	TAN CLAY - FIRM		X	1	150	190	LT. BROWN CLAY - FIRM w/ Voids		X	1	190	220	UPPER Dk. Bk. Sediment - FIRM		X	8 1/8	220	300	BASALT - HARD, FRAGS.		X	8	300	358	BASALT - VERY HARD		X	8	358	362	BASALT - FRAGS.		X	8	362	370	BROWN CLAY - FIRM		X	8	370	378	TAN CLAY - "		X	8	378	380	BROWN CLAY - "		X	8	380	425	BASALT - MED. FRAGS., 2 GPM K		X	8	425	465	TAN CLAY - FIRM		X	8	465	470	BROWN CLAY - "		X	8	470	490	BASALT - MED. FRAGS.		X	8	490	500	20-50 GPM BASALT - HARD		X
Bore Diam.	Depth		Material		Water																																																																																																														
	From	To		Yes	No																																																																																																														
10	0	1	TOP SOIL		X																																																																																																														
10	1	5	BROWN CLAY - CRACKS		X																																																																																																														
10 1/8	5	75	BASALT - HARD, FRAGS.		X																																																																																																														
1	75	150	TAN CLAY - FIRM		X																																																																																																														
1	150	190	LT. BROWN CLAY - FIRM w/ Voids		X																																																																																																														
1	190	220	UPPER Dk. Bk. Sediment - FIRM		X																																																																																																														
8 1/8	220	300	BASALT - HARD, FRAGS.		X																																																																																																														
8	300	358	BASALT - VERY HARD		X																																																																																																														
8	358	362	BASALT - FRAGS.		X																																																																																																														
8	362	370	BROWN CLAY - FIRM		X																																																																																																														
8	370	378	TAN CLAY - "		X																																																																																																														
8	378	380	BROWN CLAY - "		X																																																																																																														
8	380	425	BASALT - MED. FRAGS., 2 GPM K		X																																																																																																														
8	425	465	TAN CLAY - FIRM		X																																																																																																														
8	465	470	BROWN CLAY - "		X																																																																																																														
8	470	490	BASALT - MED. FRAGS.		X																																																																																																														
8	490	500	20-50 GPM BASALT - HARD		X																																																																																																														
5. WELL CONSTRUCTION Casing schedule: ☒ Steel ☐ Concrete ☐ Other _____ <table border="1"><thead><tr><th>Thickness</th><th>Diameter</th><th>From</th><th>To</th></tr></thead><tbody><tr><td><u>.250</u> inches</td><td><u>6</u> inches</td><td><u>2</u> feet</td><td><u>258</u> feet</td></tr><tr><td>_____ inches</td><td>_____ inches</td><td>_____ feet</td><td>_____ feet</td></tr><tr><td>_____ inches</td><td>_____ inches</td><td>_____ feet</td><td>_____ feet</td></tr><tr><td>_____ inches</td><td>_____ inches</td><td>_____ feet</td><td>_____ feet</td></tr></tbody></table> Was casing drive shoe used? ☒ Yes ☐ No Was a packer or seal used? ☐ Yes ☒ No Perforated? ☐ Yes ☒ No How perforated? ☐ Factory ☐ Knife ☐ Torch Size of perforation _____ inches by _____ inches <table border="1"><thead><tr><th>Number</th><th>From</th><th>To</th></tr></thead><tbody><tr><td>_____ perforations</td><td>_____ feet</td><td>_____ feet</td></tr><tr><td>_____ perforations</td><td>_____ feet</td><td>_____ feet</td></tr><tr><td>_____ perforations</td><td>_____ feet</td><td>_____ feet</td></tr></tbody></table> Well screen installed? ☐ Yes ☒ No Manufacturer's name _____ Type _____ Model No. _____ Diameter _____ Slot size _____ Set from _____ feet to _____ feet Diameter _____ Slot size _____ Set from _____ feet to _____ feet Gravel packed? ☐ Yes ☒ No ☐ Size of gravel _____ Placed from _____ feet to _____ feet Surface seal depth <u>20+</u> Material used in seal: ☐ Cement grout ☒ Bentonite ☐ Pudding clay ☐ _____ Sealing procedure used: ☐ Slurry pit ☐ Temp. surface casing ☐ Overbore to seal depth Method of joining casing: ☐ Threaded ☒ Welded ☐ Solvent Weld _____ ☐ Cemented between strata Describe access port <u>4" OPENING</u>		Thickness	Diameter	From	To	<u>.250</u> inches	<u>6</u> inches	<u>2</u> feet	<u>258</u> feet	_____ inches	_____ inches	_____ feet	_____ feet	_____ inches	_____ inches	_____ feet	_____ feet	_____ inches	_____ inches	_____ feet	_____ feet	Number	From	To	_____ perforations	_____ feet	_____ feet	_____ perforations	_____ feet	_____ feet	_____ perforations	_____ feet	_____ feet	10. WORK STARTED <u>11/1</u> finished <u>11/3/89</u>																																																																																	
Thickness	Diameter	From	To																																																																																																																
<u>.250</u> inches	<u>6</u> inches	<u>2</u> feet	<u>258</u> feet																																																																																																																
_____ inches	_____ inches	_____ feet	_____ feet																																																																																																																
_____ inches	_____ inches	_____ feet	_____ feet																																																																																																																
_____ inches	_____ inches	_____ feet	_____ feet																																																																																																																
Number	From	To																																																																																																																	
_____ perforations	_____ feet	_____ feet																																																																																																																	
_____ perforations	_____ feet	_____ feet																																																																																																																	
_____ perforations	_____ feet	_____ feet																																																																																																																	
6. LOCATION OF WELL Sketch map location must agree with written location. <table border="1"><tr><td>N</td><td></td><td></td><td></td><td></td></tr><tr><td>W</td><td></td><td>K</td><td></td><td>E</td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr></table> County <u>KOOTENAI</u> Subdivision Name <u>S 1/2 X S 1/2, 60th NAT. 2</u> Lot No. _____ Block No. _____		N					W		K		E																11. DRILLERS CERTIFICATION I certify that all minimum well construction standards were complied with at the time the rig was removed. Firm Name <u>S. J. Dorsay & Son</u> License No. <u>319</u> Address <u>5123 LINKS RD.</u> Date <u>11/7/89</u> Signed by (Firm Official) <u>Charles R. Johnson</u> and <u>Bob Johnson</u> (Operator)																																																																																								
N																																																																																																																			
W		K		E																																																																																																															
12. LOCATION OF WELL Sketch map location must agree with written location. <table border="1"><tr><td>N</td><td></td><td></td><td></td><td></td></tr><tr><td>W</td><td></td><td>K</td><td></td><td>E</td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr></table> County <u>KOOTENAI</u> Subdivision Name <u>S 1/2 X S 1/2, 60th NAT. 2</u> Lot No. _____ Block No. _____		N					W		K		E																13. DRILLERS CERTIFICATION I certify that all minimum well construction standards were complied with at the time the rig was removed. Firm Name <u>S. J. Dorsay & Son</u> License No. <u>319</u> Address <u>5123 LINKS RD.</u> Date <u>11/7/89</u> Signed by (Firm Official) <u>Charles R. Johnson</u> and <u>Bob Johnson</u> (Operator)																																																																																								
N																																																																																																																			
W		K		E																																																																																																															