Form 238-7
9/82

STATE OF IDAHO
DEPARTMENT OF WATER RESOURCES

WELL DRILLER'S REPORT

State law requires that this report be filed with the Director, Department of Water Resources within 30 days after the completion or abandonment of the well.

USE TYPEWRITER OR BALLPOINT PEN

RECEIVED
MAY 1 1984
Department of Water Resources
Northern District Office

N

1. WELL OWNER

Name Mr + Mrs Ray Reamer
Address Box 443 Blanchard, Idaho 83804
Owner's Permit No. 96-84-N-94

2. NATURE OF WORK

☒ New well ☐ Deepened ☐ Replacement
☐ Abandoned (describe abandonment procedures such as materials, plug depths, etc. in lithologic log)

3. PROPOSED USE

☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal
☐ Industrial ☐ Stock ☐ Waste Disposal or Injection
☐ Other _____ (specify type)

4. METHOD DRILLED

☒ Rotary ☒ Air ☐ Hydraulic ☐ Reverse rotary
☒ Cable ☐ Dug ☐ Other _____

5. WELL CONSTRUCTION

Casing schedule: ☒ Steel ☐ Concrete ☐ Other _____

Thickness	Diameter	From	To
.250 inches	6 inches	+ 1 feet	155 feet
_____ inches	_____ inches	_____ feet	_____ feet
_____ inches	_____ inches	_____ feet	_____ feet
_____ inches	_____ inches	_____ feet	_____ feet

Was casing drive shoe used? ☒ Yes ☐ No
Was a packer or seal used? ☒ Yes ☐ No
Perforated? ☐ Yes ☒ No
How perforated? ☐ Factory ☐ Knife ☐ Torch
Size of perforation _____ inches by _____ inches

Number	From	To
_____ perforations	_____ feet	_____ feet
_____ perforations	_____ feet	_____ feet
_____ perforations	_____ feet	_____ feet

Well screen installed? ☒ Yes ☐ No
Manufacturer's name JOHNSON
Type STAINLESS Model No. _____
Diameter 6 Slot size .40 Set from 155 feet to 160 feet
Diameter ___ Slot size ___ Set from ___ feet to ___ feet
Gravel packed? ☐ Yes ☒ No ☐ Size of gravel _____
Placed from _____ feet to _____ feet
Surface seal depth 18+ Material used in seal: ☐ Cement grout ☒ Bentonite ☒ Puddling clay ☐ _____
Sealing procedure used: ☐ Slurry pit ☒ Temp. surface casing ☐ Overbore to seal depth
Method of joining casing: ☐ Threaded ☐ Welded ☐ Solvent Weld ☐ Cemented between strata
Describe access port _____

6. LOCATION OF WELL

Sketch map location must agree with written location.

N / W / E / S

Subdivision Name Spirit Valley Farms
Lot No. 1 Block No. 1
County Bonner
¼ ¼ Sec. 22, T. 54 N S, R. 5 E W

7. WATER LEVEL

Static water level 128 feet below land surface.
Flowing? ☐ Yes ☒ No G.P.M. flow _____
Artesian closed-in pressure _____ p.s.i.
Controlled by: ☐ Valve ☐ Cap ☐ Plug
Temperature 56 °F. Quality clear
Describe artesian or temperature zones below.

8. WELL TEST DATA

☐ Pump ☒ Bailer ☐ Air ☐ Other _____

Discharge G.P.M.	Pumping Level	Hours Pumped
15+	0 drawdown	1

9. LITHOLOGIC LOG

Bore Diam.	Depth From	Depth To	Material	Water Yes	Water No
8	0	20	top soil + Coarse sand		2
	20	160	Coarse sand + gravel	✓	
	140	160	water sand + gravel	✓	

RECEIVED APPROVED
004339

10.

Work started 4-17-84 finished 4-20-84

11. DRILLERS CERTIFICATION

I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Firm Name Intermountain Drilling Firm No. 252
Address Priest River, Idaho Date 4-28-84
Signed by (Firm Official) Bernard D. Hoyer
and
(Operator) Same

USE ADDITIONAL SHEETS IF NECESSARY — FORWARD THE WHITE COPY TO THE DEPARTMENT