


STATE OF IDAHO
DEPARTMENT OF WATER RESOURCESUSE TYPEWRITER OR
BALLPOINT PEN

WELL DRILLER'S REPORT

State law requires that this report be filed with the Director, Department of Water Resources
within 30 days after the completion or abandonment of the well.

1. WELL OWNER Name <u>DAVE THIESEN</u> Address <u>1905 N. Fairway, Cda.</u> Drilling Permit No. <u>92-92-N-5</u> Water Right Permit No. _____	7. WATER LEVEL Static water level <u>115</u> feet below land surface. Flowing? ☐ Yes ☒ No G.P.M. flow _____ Artesian closed-in pressure _____ p.s.i. Controlled by: ☐ Valve ☐ Cap ☐ Plug Temperature _____ of. Quality _____ Describe artesian or temperature zones below																																																																																																				
2. NATURE OF WORK ☒ New well ☐ Deepened ☐ Replacement ☐ Well diameter increase ☐ Abandoned (describe abandonment procedures such as materials, plug depths, etc. in lithologic log)	8. WELL TEST DATA ☐ Pump ☐ Bailer ☒ Air ☐ Other _____ <table border="1" style="width: 100%; border-collapse: collapse;"><tr><th>Discharge G.P.M.</th><th>Pumping Level</th><th>Hours Pumped</th></tr><tr><td><u>15</u></td><td><u>260</u></td><td><u>1</u></td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr></table>	Discharge G.P.M.	Pumping Level	Hours Pumped	<u>15</u>	<u>260</u>	<u>1</u>																																																																																														
Discharge G.P.M.	Pumping Level	Hours Pumped																																																																																																			
<u>15</u>	<u>260</u>	<u>1</u>																																																																																																			
3. PROPOSED USE ☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal ☐ Industrial ☐ Stock ☐ Waste Disposal or Injection ☐ Other _____ (specify type)	9. LITHOLOGIC LOG 85057 <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th rowspan="2">Bore Diam.</th><th colspan="2">Depth</th><th rowspan="2">Material</th><th colspan="2">Water</th></tr><tr><th>From</th><th>To</th><th>Yes</th><th>No</th></tr></thead><tbody><tr><td>8</td><td>0</td><td>7</td><td>CLAY, BROWN, HARD</td><td></td><td>X</td></tr><tr><td>8</td><td>7</td><td>19</td><td>BASALT, BLACK, MED. HARD</td><td></td><td>X</td></tr><tr><td>6</td><td>19</td><td>24</td><td>BASALT, BLACK, MED. HARD</td><td></td><td>X</td></tr><tr><td>24</td><td>24</td><td>35</td><td>BASALT, BROWN, DECOMPOSED</td><td></td><td>X</td></tr><tr><td>35</td><td>35</td><td>107</td><td>BASALT, BLACK, MED. HARD</td><td></td><td>X</td></tr><tr><td>107</td><td>107</td><td>108</td><td>BASALT, BLACK, FRAG. (2 GPM)</td><td>X</td><td></td></tr><tr><td>108</td><td>108</td><td>128</td><td>BASALT, BLACK, DECOMPOSED</td><td></td><td>X</td></tr><tr><td>128</td><td>128</td><td>207</td><td>BASALT, BLACK/GREEN, DECOMP.</td><td></td><td>X</td></tr><tr><td>207</td><td>207</td><td>224</td><td>CLAY, BROWN, HARD</td><td></td><td>X</td></tr><tr><td>224</td><td>224</td><td>235</td><td>SHALE, BROWN, CLAY BINDER</td><td></td><td>X</td></tr><tr><td>235</td><td>235</td><td>239</td><td>SHALE, BROWN/RED, SOFT</td><td></td><td>X</td></tr><tr><td>239</td><td>239</td><td>241</td><td>SHALE, GRAYEL (5 GPM)</td><td>X</td><td></td></tr><tr><td>241</td><td>241</td><td>250</td><td>SHALE, BROWN/RED, SOFT</td><td></td><td>X</td></tr><tr><td>250</td><td>250</td><td>251</td><td>SHALE, FRACTURE (8 GPM)</td><td>X</td><td></td></tr><tr><td>251</td><td>251</td><td>263</td><td>SHALE, BROWN/RED, SOFT</td><td></td><td>X</td></tr></tbody></table>	Bore Diam.	Depth		Material	Water		From	To	Yes	No	8	0	7	CLAY, BROWN, HARD		X	8	7	19	BASALT, BLACK, MED. HARD		X	6	19	24	BASALT, BLACK, MED. HARD		X	24	24	35	BASALT, BROWN, DECOMPOSED		X	35	35	107	BASALT, BLACK, MED. HARD		X	107	107	108	BASALT, BLACK, FRAG. (2 GPM)	X		108	108	128	BASALT, BLACK, DECOMPOSED		X	128	128	207	BASALT, BLACK/GREEN, DECOMP.		X	207	207	224	CLAY, BROWN, HARD		X	224	224	235	SHALE, BROWN, CLAY BINDER		X	235	235	239	SHALE, BROWN/RED, SOFT		X	239	239	241	SHALE, GRAYEL (5 GPM)	X		241	241	250	SHALE, BROWN/RED, SOFT		X	250	250	251	SHALE, FRACTURE (8 GPM)	X		251	251	263	SHALE, BROWN/RED, SOFT		X
Bore Diam.	Depth		Material	Water																																																																																																	
	From	To		Yes	No																																																																																																
8	0	7	CLAY, BROWN, HARD		X																																																																																																
8	7	19	BASALT, BLACK, MED. HARD		X																																																																																																
6	19	24	BASALT, BLACK, MED. HARD		X																																																																																																
24	24	35	BASALT, BROWN, DECOMPOSED		X																																																																																																
35	35	107	BASALT, BLACK, MED. HARD		X																																																																																																
107	107	108	BASALT, BLACK, FRAG. (2 GPM)	X																																																																																																	
108	108	128	BASALT, BLACK, DECOMPOSED		X																																																																																																
128	128	207	BASALT, BLACK/GREEN, DECOMP.		X																																																																																																
207	207	224	CLAY, BROWN, HARD		X																																																																																																
224	224	235	SHALE, BROWN, CLAY BINDER		X																																																																																																
235	235	239	SHALE, BROWN/RED, SOFT		X																																																																																																
239	239	241	SHALE, GRAYEL (5 GPM)	X																																																																																																	
241	241	250	SHALE, BROWN/RED, SOFT		X																																																																																																
250	250	251	SHALE, FRACTURE (8 GPM)	X																																																																																																	
251	251	263	SHALE, BROWN/RED, SOFT		X																																																																																																
4. METHOD DRILLED ☒ Rotary ☒ Air ☐ Hydraulic ☐ Reverse rotary ☐ Cable ☐ Dug ☐ Other _____	RECEIVED JUL 31 1992 NORTHERN REGION IDWR RECEIVED AUG 24 1992 Department of Water Resources DEC 04 1992																																																																																																				
5. WELL CONSTRUCTION Casing schedule: ☒ Steel ☐ Concrete ☐ Other _____ <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>Thickness</th><th>Diameter</th><th>From</th><th>To</th></tr></thead><tbody><tr><td><u>250</u> inches</td><td><u>6</u> inches</td><td><u>1</u> feet</td><td><u>19</u> feet</td></tr><tr><td><u>200 PSI</u> inches</td><td><u>4" PVC</u> inches</td><td><u>6</u> feet</td><td><u>263</u> feet</td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr></tbody></table> Was casing drive shoe used? ☒ Yes ☐ No Was a packer or seal used? ☐ Yes ☒ No Perforated? ☒ Yes ☐ No <u>SKILL SAW</u> How perforated? ☐ Factory ☐ Knife ☐ Torch ☐ Gun Size of perforation <u>1/4</u> inches by <u>6</u> inches Number <u>120</u> perforations From <u>223</u> feet To <u>263</u> feet perforations feet feet perforations feet feet Well screen installed? ☐ Yes ☒ No Manufacturer's name _____ Type _____ Model No. _____ Diameter _____ Slot size _____ Set from _____ feet to _____ feet Diameter _____ Slot size _____ Set from _____ feet to _____ feet Gravel packed? ☐ Yes ☒ No ☐ Size of gravel _____ Placed from _____ feet to _____ feet Surface seal depth <u>19</u> Material used in seal: ☐ Cement grout ☒ Bentonite ☐ Puddling clay ☐ _____ Sealing procedure used: ☐ Slurry pit ☐ Temp. surface casing ☒ Overbore to seal depth Method of joining casing: ☐ Threaded ☐ Welded ☐ Solvent Weld ☐ Cemented between strata Describe access port _____	Thickness	Diameter	From	To	<u>250</u> inches	<u>6</u> inches	<u>1</u> feet	<u>19</u> feet	<u>200 PSI</u> inches	<u>4" PVC</u> inches	<u>6</u> feet	<u>263</u> feet																																																																																									
Thickness	Diameter	From	To																																																																																																		
<u>250</u> inches	<u>6</u> inches	<u>1</u> feet	<u>19</u> feet																																																																																																		
<u>200 PSI</u> inches	<u>4" PVC</u> inches	<u>6</u> feet	<u>263</u> feet																																																																																																		
6. LOCATION OF WELL Sketch map location <u>must</u> agree with written location.  Subdivision Name _____ Lot No. _____ Block No. _____ County <u>Banah</u> NE 1/4 SW 1/4 Sec. <u>26</u>, T. <u>45</u> N. R. <u>3</u> E. W. <u> </u>	11. DRILLERS CERTIFICATION I/We certify that all minimum well construction standards were complied with at the time the rig was removed. Firm Name <u>H2O Well Svc.</u> Firm No. <u>448</u> Address <u>Hayden Lk. Id</u> Date <u>7-20-92</u> Signed by (Firm Official) <u>Burt J. Cuff</u> and (Operator) <u>Anthony C. Kaut</u>																																																																																																				