




WELL DRILLER'S REPORT

State law requires that this report be filed with the Director, Department of Water Resources within 30 days after the completion or abandonment of the well.

1. WELL OWNER Name <u>Mr John Tanner</u> Address <u>HCO2 Box 161 M Harrison ID</u> Drilling Permit No. <u>95-91-A-93</u> Water Right Permit No. _____	7. WATER LEVEL Static water level <u>265</u> feet below land surface. Flowing? ☐ Yes ☒ No G.P.M. flow _____ Artesian closed-in pressure _____ p.s.i. Controlled by: ☐ Valve ☐ Cap ☐ Plug Temperature _____ OF. Quality _____ <i>Describe artesian or temperature zones below.</i>																											
2. NATURE OF WORK ☒ New well ☐ Deepened ☐ Replacement ☐ Well diameter increase ☐ Abandoned (describe abandonment procedures such as materials, plug depths, etc. in lithologic log)	8. WELL TEST DATA ☐ Pump ☐ Bailor ☒ Air ☐ Other _____ <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Discharge G.P.M.</th> <th>Pumping Level</th> <th>Hours Pumped</th> </tr> </thead> <tbody> <tr> <td><u>20+ gpm</u></td> <td></td> <td></td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>	Discharge G.P.M.	Pumping Level	Hours Pumped	<u>20+ gpm</u>																							
Discharge G.P.M.	Pumping Level	Hours Pumped																										
<u>20+ gpm</u>																												
3. PROPOSED USE ☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal ☐ Industrial ☐ Stock ☐ Waste Disposal or Injection ☐ Other _____ (specify type)	9. LITHOLOGIC LOG <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Bore Diam.</th> <th colspan="2">Depth</th> <th rowspan="2">Material</th> <th rowspan="2">Water Yes No</th> </tr> <tr> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr> <td>8"</td> <td>0</td> <td>80</td> <td>Clay To Basalt water</td> <td>+</td> </tr> <tr> <td>8"</td> <td>80</td> <td>170</td> <td>Basalt</td> <td>+</td> </tr> <tr> <td>6"</td> <td>170</td> <td>385</td> <td>Clay-sand</td> <td>+</td> </tr> <tr> <td>6"</td> <td>385</td> <td>360</td> <td>Basalt</td> <td>+</td> </tr> </tbody> </table>	Bore Diam.	Depth		Material	Water Yes No	From	To	8"	0	80	Clay To Basalt water	+	8"	80	170	Basalt	+	6"	170	385	Clay-sand	+	6"	385	360	Basalt	+
Bore Diam.	Depth		Material	Water Yes No																								
	From	To																										
8"	0	80	Clay To Basalt water	+																								
8"	80	170	Basalt	+																								
6"	170	385	Clay-sand	+																								
6"	385	360	Basalt	+																								
4. METHOD DRILLED ☒ Rotary ☒ Air ☐ Hydraulic ☐ Reverse rotary ☐ Cable ☐ Dug ☐ Other _____	 Department of Water Resources																											
5. WELL CONSTRUCTION Casing schedule: ☒ Steel ☐ Concrete ☐ Other <u>AVC</u> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Thickness</th> <th>Diameter</th> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr> <td><u>.750</u> inches</td> <td><u>6</u> inches</td> <td><u>2</u> feet</td> <td><u>285</u> feet</td> </tr> <tr> <td><u>AVC</u> inches</td> <td><u>4</u> inches</td> <td><u>280</u> feet</td> <td><u>360</u> feet</td> </tr> <tr> <td>_____ inches</td> <td>_____ inches</td> <td>_____ feet</td> <td>_____ feet</td> </tr> <tr> <td>_____ inches</td> <td>_____ inches</td> <td>_____ feet</td> <td>_____ feet</td> </tr> </tbody> </table> Was casing drive shoe used? ☒ Yes ☐ No Was a packer or seal used? ☐ Yes ☒ No Perforated? <u>Liner</u> ☐ Yes ☐ No <u>saw</u> How perforated? ☐ Factory ☐ Knife ☐ Torch ☐ Gun Size of perforation <u>1/8</u> inches by <u>4</u> inches Number _____ From _____ To _____ <u>200</u> perforations _____ feet _____ feet _____ perforations _____ feet _____ feet _____ perforations _____ feet _____ feet Well screen installed? ☐ Yes ☐ No Manufacturer's name _____ Type _____ Model No. _____ Diameter _____ Slot size _____ Set from _____ feet to _____ feet Diameter _____ Slot size _____ Set from _____ feet to _____ feet Gravel packed? ☐ Yes ☐ No ☐ Size of gravel _____ Placed from _____ feet to _____ feet Surface seal depth _____ Material used in seal: ☐ Cement grout ☒ Bentonite ☐ Puddling clay ☐ Cuffing Sealing procedure used: ☐ Slurry pit ☐ Temp. surface casing ☒ Overbore to seal depth Method of joining casing: ☐ Threaded ☒ Welded ☐ Solvent Weld ☐ Cemented between strata Describe access port _____	Thickness	Diameter	From	To	<u>.750</u> inches	<u>6</u> inches	<u>2</u> feet	<u>285</u> feet	<u>AVC</u> inches	<u>4</u> inches	<u>280</u> feet	<u>360</u> feet	_____ inches	_____ inches	_____ feet	_____ feet	_____ inches	_____ inches	_____ feet	_____ feet	 IDWR							
Thickness	Diameter	From	To																									
<u>.750</u> inches	<u>6</u> inches	<u>2</u> feet	<u>285</u> feet																									
<u>AVC</u> inches	<u>4</u> inches	<u>280</u> feet	<u>360</u> feet																									
_____ inches	_____ inches	_____ feet	_____ feet																									
_____ inches	_____ inches	_____ feet	_____ feet																									
6. LOCATION OF WELL Sketch map location must agree with written _____  Subdivision Name _____ Lot No. _____ Block No. _____ County <u>Kootenai</u> N ☒ NE ☐ SE ☐ S ☐ SW ☐ W ☐ R. <u>3</u>	10. Work started <u>7-2-91</u> finished <u>7-9-91</u>																											
11. DRILLERS CERTIFICATION I/We certify that all minimum well construction standards were complied with at the time the rig was removed. Firm Name <u>H&W Well Serv</u> Firm No. <u>448</u> Address <u>Hayden, ID</u> Date <u>7-10-91</u> Signed by (Firm Official) <u>[Signature]</u> and (Operator) <u>[Signature]</u>	MICROFILMED DEC 04 1991																											

USE ADDITIONAL SHEETS IF NECESSARY — FORWARD THE WHITE COPY TO THE DEPARTMENT