

IDAHO DEPARTMENT OF WATER RESOURCES
WELL DRILLER'S REPORT

Office Use Only			
Well ID No.			
Inspected by			
Twp	Rge	Sec	
	1/4	1/4	1/4
Lat:	:	Long:	:

1. WELL TAG NO. D DOO 41592
DRILLING PERMIT NO. 839980
Water Right or Injection Well No. _____

2. OWNER:

Name DAVID + SANDY HELLESKOY
Address 245 S.F.K. HANGMAN CR. RD.
City TENSED State ID Zip 83870

3. LOCATION OF WELL by legal description:

You must provide address or Lot, Blk. Sub. or Directions to well.

Twp. 43 North ☒ or South ☐
Rge. 4 East ☐ or West ☒
Sec. 1 1/4 S/E 1/4 S/E 1/4
Gov't Lot 2 County BENEFIT
Lat: : : Long: : :
Address of Well Site 245 S.F.K. HANGMAN CR. RD.
City TENSED

Lt. _____ Blk. _____ Sub. Name _____

4. USE:

☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation
☐ Thermal ☐ Injection ☐ Other _____

5. TYPE OF WORK check all that apply (Replacement etc.)

☒ New Well ☐ Modify ☐ Abandonment ☐ Other _____

6. DRILL METHOD:

☒ Air Rotary ☐ Cable ☐ Mud Rotary ☐ Other _____

7. SEALING PROCEDURES

Seal Material	From	To	Weight / Volume	Seal Placement Method
Bentonite	0	60	85x	Pour Around Pipe

Was drive shoe used? ☒ Y ☐ N Shoe Depth(s) 138
Was drive shoe seal tested? ☒ Y ☐ N How? Air

8. CASING/LINER:

Diameter	From	To	Gauge	Material	Casing	Liner	Welded	Threaded
6"	+2	-138	250	Steel	☒	☐	☒	☐
4"	-15	-502	160	PVC	☐	☒	☐	☐

Length of Headpipe _____ Length of Tailpipe _____
Packer ☐ Y ☒ N Type _____

9. PERFORATIONS/SCREENS PACKER TYPE

Perforation Method Drill
Screen Type & Method of Installation _____

From	To	Slot Size	Number	Diameter	Material	Casing	Liner
-382	-482	3/4	50	4"	PVC	☐	☒

10. FILTER PACK

Filter Material	From	To	Weight / Volume	Placement Method
none				

11. STATIC WATER LEVEL OR ARTESIAN PRESSURE:

Flowing ft. below ground _____ Artesian pressure _____ lb.
Depth flow encountered 470 ft. Describe access port or control devices: _____

43N 4W 1

12. WELL TESTS:

☐ Pump ☐ Bailer ☒ Air ☐ Flowing Artesian

Yield gal./min.	Drawdown	Pumping Level	Time
30 gpm	Air lift from 500'		

Water Temp. 55° Bottom hole temp. _____
Water Quality test or comments: Slightly Cloudy
Depth first Water Encounter 402

13. LITHOLOGIC LOG: (Describe repairs or abandonment)

Bore Dia.	From	To	Remarks: Lithology, Water Quality & Temperature	Y	N
8"	0	10	Clay Tan		
	10	30	Gravel + sand wet		
	30	53	Clay Red		
	53	76	Clay-Tan w/shale		
	76	100	Clay-Tan		
	100	131	Clay-Tan w/shale		
	131	138	Shale Tan		
6"	138	180	Shale Gray - soft		
	180	402	Shale Gray - Hard		
	402	403	Shale Gray w/water 2 1/2 gpm		
	403	470	Shale Gray		
	470	480	Shale Gray - Broken w/water 28 gpm		
	480	502	Shale gray		

RECEIVED
JUN 28 2006
IDWR/NOR

Completed Depth 502 (Measurable)
Date: Started 5-24-06 Completed 5-30-06

14. DRILLER'S CERTIFICATION

I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Company Name ACTION DRILLING INC Firm No. 618

Principal Driller ALVIN CARRIS Date 6-22-06

Driller or Operator II _____ Date _____

Operator I Alvin Carris Date 6-22-06

Principal Driller and Rig Operator Required.
Operator I must have signature of Driller/Operator II.