



SWSE

SESE

27

52N05W

SWSW 4

19

52N04W

NENE

25

NWNW 130

## IDAHO DEPARTMENT OF WATER RESOURCES

## WELL DRILLER'S REPORT

| Office Use Only |           |     |
|-----------------|-----------|-----|
| Inspected by    |           |     |
| Twp             | Rge       | Sec |
| 1/4             | 1/4       | 1/4 |
| Lat: : :        | Long: : : |     |

1. WELL TAG NO. D0017936Drilling Permit No: 772065

Other IDWR No. \_\_\_\_\_


## 2. OWNER

Well Number: \_\_\_\_\_

Name JOHN & LISA PORRIA 339Address 8180 SPRINGDALE CTCity GILROY State CA Zip 95020

## 3. LOCATION OF WELL by legal description

sketch map location must agree with written location

Twp. 52N ☒ North or ☐ SouthRge. 5W ☐ East or ☒ WestSec. 24 SE 1/4 SE 1/4 1/4Gov't Lot \_\_\_\_\_ County KOOTENAI

Lat: : : Long: : :

Address of Well Site RESERVOIR RD.City RATHDRUM

(Give at least name of road + Distance to Road or Landmark)

Lt. \_\_\_\_\_ Blk. \_\_\_\_\_ Sub. Name \_\_\_\_\_

## 4. USE:

☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation☐ Thermal ☐ Injection ☐ Other \_\_\_\_\_

## 5. TYPE OF WORK check all that apply (Replacement, etc.)

☒ New Well ☐ Modify ☐ Abandonment ☐ Other \_\_\_\_\_

## 6. DRILL METHOD

☒ Air Rotary ☐ Cable ☐ Mud Rotary ☐ Other \_\_\_\_\_

## 7. SEALING PROCEDURES

| SEAL/FILTER PACK |      |    | AMOUNT          | METHOD   |
|------------------|------|----|-----------------|----------|
| Material         | From | To | Sacks or Pounds |          |
| BENTONITE        | 0    | 18 | 4 BAGS          | OVERBORE |
|                  |      |    |                 |          |
|                  |      |    |                 |          |

Was drive shoe used? ☒ Y ☐ N Shoe Depth(s) 18Was drive shoe seal tested? ☐ Y ☐ N How? \_\_\_\_\_

## 8. CASING/LINER:

| Diameter | From | To  | Gauge | Material | Casing                              | Liner                               | Welded                   | Threaded                 |
|----------|------|-----|-------|----------|-------------------------------------|-------------------------------------|--------------------------|--------------------------|
| 4        | -5   | 425 | .160  | PVC      | <input type="checkbox"/>            | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 6        | +2   | 18  | .250  | STEEL    | <input checked="" type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/> |

Length of Headpipe \_\_\_\_\_ Length of Tailpipe \_\_\_\_\_

## 9. PERFORATIONS/SCREENS

☒ Perforations Method SKIL SAW☐ Screens Screen Type \_\_\_\_\_

| From | To  | Slot Size | Number | Diameter | Material | Casing                   | Liner                               |
|------|-----|-----------|--------|----------|----------|--------------------------|-------------------------------------|
| 380  | 420 | 1/8 X 6   | 170    | 4        | PVC      | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
|      |     |           |        |          |          |                          |                                     |
|      |     |           |        |          |          |                          |                                     |

## 10. STATIC WATER LEVEL OR ARTESIAN PRESSURE:

120 ft. below ground Artesian pressure \_\_\_\_\_ lb.Depth flow encountered 120 ft. Describe access port or control devices: \_\_\_\_\_

## 11. WELL TESTS:

☐ Pump ☐ Bailer ☒ Air ☐ Flowing Artesian

| Yield gal./min. | Drawdown | Pumping Level | Time |
|-----------------|----------|---------------|------|
| 6               |          | 420           | 1 HR |
|                 |          |               |      |
|                 |          |               |      |

Water Temp. COLD Bottom Hole Temp COLDWater Quality test or comments: CLEARDepth first Water encountered 120

## 12. LITHOLOGIC LOG:(Describe repairs or abandonment)

|           |      |     |                                                | Water                               |                                     |
|-----------|------|-----|------------------------------------------------|-------------------------------------|-------------------------------------|
| Bore Diam | From | To  | Remarks: Lithology, Water Quality, Temperature | Y                                   | N                                   |
| 8         | 0    | 10  | Clayish Top Soil Brown                         | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| 8         | 10   | 16  | Decomp Granite Brown                           | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| 6         | 16   | 28  | Granite Firm                                   | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| 6         | 28   | 82  | Granite Browken White & Brown                  | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| 6         | 82   | 120 | Granite Black & Copper                         | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| 6         | 120  | 130 | Granite Fractured Black, White & Gree          | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| 6         | 130  | 395 | Granite Gray Hard                              | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| 6         | 395  | 403 | Granite Green & Black w/Water apx 5            | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| 6         | 403  | 425 | Granite Gray Hard                              | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |

RECEIVED

DEC - 6 2001

IDWR North

Completed Depth 425 (Measurable)Date: Started 11/14/01 Completed 11/15/01

## 13. DRILLER'S CERTIFICATION

I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Firm Name H2O WellService, Inc. Firm No. 448Firm Official [Signature] Date 11-26-01and Supervisor or Operator [Signature] Date 11-20-01

(Sign Once if Firm Official and Operator)

Louie Hanner

52N 5W 24