



State of Idaho

DEPARTMENT OF WATER RESOURCES

Northern Region, 7600 N. Mineral Drive, Suite 100 • Coeur d'Alene, Idaho 83815

Phone: (208) 762-2800 • Fax: (208) 762-2819 • Web Site: www.idwr.idaho.gov

C. L. "BUTCH" OTTER
Governor

GARY SPACKMAN
Director

October 31, 2013

Walker Family Revocable Trust
10096 S Fire Sky Creek RD
Harrison, ID 838333-4903

Re: Coeur d'Alene-Spokane River Basin Adjudication Claim (CSRBA) Claim No. ⁹⁵94-12868

Dear Claimants:

Idaho Department of Water Resources (IDWR) has completed initial processing of your Internet CSRBA Claim to use Domestic and Stockwater from a well (Ground Water) on Kootenai County parcel 49N03W-20-3150. A copy of your Claim is enclosed.

Please contact me about conflicting information in your Claim between the quantities of water shown for Domestic and Stockwater use between the first and second pages of your Claim. This information is needed from you before IDWR can complete an accurate recommendation on your water uses to the Court.

My telephone number at the IDWR Northern Region Office is (208) 762.2816.

Respectfully,

Shaun M. Maxey
Senior Water Resource Agent
Idaho Department of Water Resources, Northern Region


Enclosures

Copy of CSRBA Claim 95-12868
Well Driller Report

IDAHO DEPARTMENT OF WATER RESOURCES WELL DRILLER'S REPORT

Office Use Only			
Inspected by _____			
Twp _____	Rge _____	Sec _____	
1/4 _____	1/4 _____	1/4 _____	
Lat: _____	Long: _____		

1. DRILLING PERMIT NO. 844535
Other IDWR No. D0053848
2. OWNER:
Name Lynn Walker
Address 42418 N. Tonto Road
City Cave Creek State AZ Zip 85331
3. LOCATION OF WELL by legal description:
Sketch map location must agree with written location

W  E
Twp. 49 North ☒ or South ☐
Rge. 3 East ☐ or West ☒
Sec. 20 1/4 NW 1/4 NW 1/4
10 acres 40 acres 160 acres
Gov't lot _____ County Kootenai
Lat: 47: _____ Long: 116: _____
Address of Well Site 3020 E. Gotham Bay Road
City Harrison

(Give at least name of road + Distance to Road or Landmark)
Lt. _____ Blk. _____ Sub. Name _____

4. USE:
☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation
☐ Thermal ☐ Injection ☐ Other _____

5. TYPE OF WORK check all that apply (Replacement etc.)
☒ New Well ☐ Modify ☐ Abandonment ☐ Other _____

6. DRILL METHOD
☒ Air Rotary ☐ Cable ☐ Mud Rotary ☐ Other _____

SEAL/FILTER PACK			AMOUNT	METHOD
Material	From	To	Sacks or Pounds	
Bentonite	0	120	1150#	Dry granular

Was drive shoe used? ☒ Y ☐ N Shoe Depth(s) 458'
Was drive shoe seal tested? ☐ Y ☒ N How? _____

Diameter	From	To	Gauge	Material	Casing	Liner	Welded	Threaded
6"	+2	458	.250	Steel	☒	☐	☒	☐
4"	20	800	S 40	PVC	☐	☒	☐	☐
					☐	☐	☐	☐

Length of Headpipe _____ Length of Tailpipe _____

9. PERFORATIONS/SCREENS
☒ Perforations Method saw cut 1/8" x 6"
☐ Screens Screen Type _____

From	To	Slot Size	Number	Diameter	Material	Casing	Liner
760	800	1/8"	60	4"	PVC	☐	☒
						☐	☐
						☐	☐

10. STATIC WATER LEVEL OR ARTESIAN PRESSURE:
286 ft. below ground Artesian Pressure _____ lb
Depth flow encountered _____ ft. Describe access port or control devices: _____

11. WELL TESTS:

☐ Pump ☐ Bailer ☒ Air ☐ Flowing Artesian

Yield gal/min.	Drawdown	Pumping Level	Time
20-25 gpm			

Water Temp. _____ Bottom hole temp. _____
Water Quality test or comments: Very silty, then clear after 6 hours developing
Depth first Water Encountered 532'

12. LITHOLOGIC LOG: (Describe repairs or abandonment)

Bore Dia	From	To	Remarks: Lithology, Water Quality & Temp.	Y	N
10"	0	2	Topsoil		☒
	2	18	Clay, tan		☒
8"	18	32	Clay, tan to brown		☒
	32	46	Clay, green		☒
	46	51	Clay, dark brown to black		☒
	51	73	Basalt w/ lenses of cobbles, bk clay		☒
	73	75	Clay, olive green		☒
	75	79	Basalt, hard		☒
	79	82	Clay, olive green		☒
	82	89	Basalt, clay		☒
	89	105	Clay, brown		☒
	105	128	Clay, tan, wet		☒
	128	143	Clay, tan, soft, wet		☒
	143	163	Clay, brown, hard		☒
	163	212	Clay, tan w/ orange lenses		☒
	212	365	Clay, tan, sand, fine, wet		☒
	365	425	Shale, dec w/ silt & ang. rock, tan		☒
	425	458	Shale, decomposed, tan		☒
6"	458	521	Shale, tan, medium hard		☒
	521	532	Shale, tan w/sm. clay lenses, tan		☒
	532	568	Shale, tan, medium		☒
	568	586	Shale, grey green		☒
	586	629	Shale, tan with soft lenses		☒
	629	685	Shale, grey green		☒
	685	711	Shale, tan, medium		☒
	711	763	Shale, grey green, hard		☒
	763	783	Shale, grey green, broken		☒
	783	796	Shale, grey green, hard		☒
	796	800	Shale, grey, broken 15 gpm		☒

Completed Depth: 800 (Measurable)
Date: Started 10/16/07 Completed 10/23/07

13. DRILLER'S CERTIFICATION

I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Firm Name McCarty Drilling & Pump Inc Firm No. 586
Firm Official [Signature] Date 10-29-07
Supervisor or Operator _____ Date _____
(Sign once if Firm Official & Operator)

Date: 10/29/2007 Time: 7:50:31 AM

49N 3W 20