

AUG 22 2000
 11/97

Office Use Only

Inspected by _____

Twp _____ Rge _____ Sec _____

_____ 1/4 _____ 1/4 _____ 1/4

Lat: : : Long: : :

1. WELL TAG NO. D 10013526
 DRILLING PERMIT NO. -
 Other IDWR No. 765859

☐ Pump ☐ Bailer☒ Air ☐ Flowing Artesian

2. OWNER: Randy Bond + Rhonda Bond
Name H C 01 Box 215 R
Address St. Maries State ID Zip 83861
City

Yield gal./min.	Drawdown	Pumping Level	Time
40 gpm	Air lift	from 215	2 hrs

Water Temp. 55.0

Bottom hole temp.

Water Quality test or comments:

Depth first Water Encounter 100

12. LITHOLOGIC LOG: (Describe repairs or abandonment)

Water

N
 Twp. 46 North ☒ or South ☐
 Rge. 2 East ☐ or West ☒
 Sec. 30 1/4 N/E 1/4 SW 1/4
 Gov't Lot _____ County Benewah
 Lat: _____ Long: _____
 S
 Address of Well Site 780 Wagon
Wheel Rd City St. Maries
 (Give at least name of road + Distance to Road or Landmark)

Bore Dia.	From	To	Remarks: Lithology, Water Quality & Temperature	Y	N
8"	0	3	Sand - Red		
	5	8	Basalt - Gray - Broken		
	8	18	Basalt - Gray - Hard		
6"	18	52	Basalt - Gray - Hard		
	52	63	Clay - Tan		
	63	95	Clay - Brown		
	95	160	Basalt - Gray		
	160	190	Basalt - Red		X
			40 g.p.m.		
	190	215	Basalt - Red w/clay		

Lt. _____ Blk. _____ Sub. Name _____

4. USE:

☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation
☐ Thermal ☐ Injection ☐ Other

5. TYPE OF WORK check all that apply (Replacement etc.)

☒ New Well ☐ Modify ☐ Abandonment ☐ Other _____

6. DRILL METHOD

☒ Air Rotary ☐ Cable ☐ Mud Rotary ☐ Other _____

7. SEALING PROCEDURES

SEAL/FILTER		PACK		AMOUNT	METHOD
Material	From	To	Sacks or Pounds		
Bentonite	0	18'	7.3X	Pour Around Pipe	

Was drive shoe used? ☒ Y ☐ N Shoe Depth(s) 18'
Was drive shoe seal tested? ☐ Y ☒ N How? Air Pressure

8. CASING/LINER:

Diameter	From	To	Gauge	Material	Casing	Liner	Welded	Threaded
6"	+2	18	225	STEEL	☒	☐	☒	☐
4"	-10	21.5	160	PVC	☐	☒	☐	☐
					☐	☐	☐	☐

Length of Headpipe_____ Length of Tailpipe_____

9. PERFORATIONS/SCREENS

Perforations Method Drill
Screens Screen Type

From	To	Slot Size	Number	Diameter	Material	Casing	liner
165	195	~~3~~	~~40~~	1/2	PVC	☐	☒
						☐	☐
						☐	☐

10. STATIC WATER LEVEL OR ARTESIAN PRESSURE:

179 ft. below ground Artesian pressure _____ lb.
Depth flow encountered 160 ft. Describe access port or
control devices: Well Cap
46N 2W 30

Completed Depth 215 (Measurable)
Date: Started Aug 1, 2000 Completed Aug 3, 2000

13. DRILLER'S CERTIFICATION

I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Company Name Altways Drilling Inc Firm No. 570

Firm Official [Signature] Date 8-13-2000

and
Driller or Operator Alvin Carris Date 8-13-2000

(Sign once if Firm Official & Operator)

FORWARD WHITE COPY TO WATER RESOURCES