

UNIT #1

RECEIVED

11/4/98 db

Form 238-7
11/97

OCT 26 1998

IDAHO DEPARTMENT OF WATER RESOURCES

IDWR/North

WELL DRILLER'S REPORT

77519

1. WELL TAG NO. D - 000 5485

RECEIVED

DRILLING PERMIT NO. 92-98-N 24

Other IDWR No.

OCT 26 1998

2. OWNER:

Name DALE HUND


Address 99810 N. Newport Hwy #165

City SPOKANE

State ID Zip 99218

3. LOCATION OF WELL by legal description:

Sketch map location must agree with written location.



Twp. 43

Rge. 1

Sec. 06

Gov't Lot

Lat.

Long.

North

East

NE

County

BENEDICT

Address of Well Site

City

FERNWOOD

City

Name

RP-43N DIED 000008-A

4. USE:

☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation
☐ Thermal ☐ Injection ☐ Other

5. TYPE OF WORK check all that apply (Replacement etc.)

☒ New Well ☐ Modify ☐ Abandonment ☐ Other

6. DRILL METHOD

☒ Air Rotary ☐ Cable ☐ Mud Rotary ☐ Other

7. SEALING PROCEDURES

SEAL/FILTER PACK		AMOUNT		METHOD
Material	From To	Sacks or Pounds		
Benite	1 30	400 LB		Trimming

Was drive shoe used? ☒ Y ☐ N Shoe Depth(s) 50Was drive shoe seal tested? ☐ Y ☐ N How?

8. CASING/LINER:

Diameter	From To	Gauge	Material	Casing	Liner	Welded	Threaded
6	1 50	250	Steel	☒	☐	☒	☐

Length of Headpipe Length of Tailpipe

9. PERFORATIONS/SCREENS

Perforations Method

Screens Screen Type

From To	Slot Size	Number	Diameter	Material	Casing	Liner
280 460	3/8	90	4"	PVC	☐	☒
-1 380		30	4"	PVC	☐	☒

10. STATIC WATER LEVEL OR ARTESIAN PRESSURE:

40 ft. below ground Artesian pressure 1b.

Depth flow encountered ft. Describe access port or

control devices:

11. WELL TESTS:

☐ Pump ☐ Bailor ☒ Air ☐ Flowing Artesian

Yield gal./min.	Drawdown	Pumping Level	Time
Est. 30 GAL. Min.			

Water Temp. Cold

Bottom hole temp. Cold

Water Quality test or comments:

Depth first Water Encounter 335 ft.

12. LITHOLOGIC LOG: (Describe repairs or abandonment)

Water

Bore Dia	From To	Remarks: Lithology, Water Quality & Temperature	Y	N
8	1 3	Top Soil		X
8	3 12	Brown clay		X
8	12 60	Basalt		X
8	60 73	Brown clay		X
8	73 113	Red clay		X
8	113 130	Broken shale		X
8	130 150	Brown clay		X
8	150 220	Red clay		X
8	220 240	Brown clay		X
8	240 260	Broken shale		X
6	260 330	Shale Rock		X
6	330 460	Broken shale Rock	X	

Completed Depth 460 (Measurable)

Date: Started 10/2/98 Completed

13. DRILLER'S CERTIFICATION

I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Company Name Precision Drilling Firm No. 558

Firm Official Date 10/1/98

and

Driller or Operator Date 10/1/98

(Sign once if Firm Official & Operator)

43 N 1E 6

FORWARD WHITE COPY TO WATER RESOURCES