

IDAHO DEPARTMENT OF WATER RESOURCES

WELL DRILLER'S REPORT

1. WELL TAG NO. D 00 ~~32845~~ 28843
DRILLING PERMIT NO. 809893
Water Right or Injection Well No. _____

2. OWNER:

Name Paul MANG HAND
Address P.O. Box 25
City St. John State WA Zip 99171

3. LOCATION OF WELL by legal description:

You must provide address or Lot, Blk, Sub. or Directions to well.

Twp. 44 North ☒ or South ☐
Rge. 2 East ☐ or West ☒
Sec. 28 1/4 NE 1/4 SE 1/4
Gov't Lot _____ County Bene WAH

Lat: _____ Long: _____
Address of Well Site 1 mile E. of E Mid 2
City EMid 2
Lt. _____ Blk. _____ Sub. Name _____

4. USE:

☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation
☐ Thermal ☐ Injection ☐ Other _____

5. TYPE OF WORK check all that apply

☒ New Well ☐ Modify ☐ Abandonment ☐ Other _____ (Replacement etc.)

6. DRILL METHOD:

☒ Air Rotary ☐ Cable ☐ Mud Rotary ☐ Other _____

7. SEALING PROCEDURES

Seal Material	From	To	Weight / Volume	Seal Placement Method
<u>Bentonite</u>	<u>0</u>	<u>18</u>	<u>430#</u>	<u>TOP Pour</u>

Was drive shoe used? ☐ Y ☒ N Shoe Depth(s) _____
Was drive shoe seal tested? ☐ Y ☐ N How? _____

8. CASING/LINER:

Diameter	From	To	Gauge	Material	Casing	Liner	Welded	Threaded
<u>6"</u>	<u>+2</u>	<u>-18</u>	<u>250</u>	<u>Steel</u>	☒	☐	☒	☐
<u>4.5"</u>	<u>-5</u>	<u>-150</u>	<u>160</u>	<u>PVC</u>	☐	☒	☐	☐

Length of Headpipe _____ Length of Tailpipe _____
Packer ☐ Y ☒ N Type _____

9. PERFORATIONS/SCREENS PACKER TYPE

Perforation Method SAW
Screen Type & Method of Installation _____

From	To	Slot Size	Number	Diameter	Material	Casing	Liner
<u>130</u>	<u>150</u>	<u>1/8 x 4</u>	<u>36</u>	<u>4.5</u>	<u>PVC</u>	☐	☒

10. FILTER PACK

Filter Material	From	To	Weight / Volume	Placement Method

11. STATIC WATER LEVEL OR ARTESIAN PRESSURE:

87 ft. below ground Artesian pressure _____ lb.
Depth flow encountered _____ ft. Describe access port or control devices: _____

Top of casing
44N 2W 28

Office Use Only		
Well ID No.		
Inspected by		
Twp	Rge	Sec
1/4	1/4	1/4
Lat:	Long:	

12. WELL TESTS:

☐ Pump ☐ Bailor ☒ Air ☐ Flowing Artesian

Yield gal./min.	Drawdown	Pumping Level	Time
<u>20</u>			<u>1.5</u>

Water Temp. 55° Bottom hole temp. _____

Water Quality test or comments: Good

Depth first Water Encounter 130'

13. LITHOLOGIC LOG: (Describe repairs or abandonment)

Bore Dia.	From	To	Remarks: Lithology, Water Quality & Temperature	Water	Y	N
<u>10</u>	<u>0</u>	<u>12</u>	<u>Clay</u>			
<u>10</u>	<u>12</u>	<u>18</u>	<u>Soft Granite</u>			
<u>6</u>	<u>18</u>	<u>21</u>	<u>" "</u>			
<u>6</u>	<u>21</u>	<u>90</u>	<u>Soft Clay</u>			
<u>6</u>	<u>90</u>	<u>130</u>	<u>Hard Blk Bslt</u>			
<u>6</u>	<u>130</u>	<u>150</u>	<u>Soft Blk Bslt</u>	<u>20</u>		

RECEIVED

JAN 22 2004

IDWR/North

RECEIVED

NOV 21 2003

IDWR/North

Completed Depth 150 (Measurable)

Date: Started 5-26-03 Completed 5-26-03

14. DRILLER'S CERTIFICATION

I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Company Name UHLERKOTT Well Drilling Firm No. 125

Principal Driller [Signature] Date 11-13-03

Driller or Operator II _____ Date _____

Operator I _____ Date _____

Principal Driller and Rig Operator Required.
Operator I must have signature of Driller/Operator II.