RECEIVED

Form 238-7
3/95 MAY 1 3 1998

IDAHO DEPARTMENT OF WATER RESOURCES
WELL DRILLER'S REPORT

Use Typewriter or Ballpoint Pen

POSTED 777726


NORTHERN REGION
IDWR

Office Use Only
Inspected by _____
Twp____ Rge____ Sec____
____1/4 ____1/4 ____1/4
Lat: : : Long: : :

1. DRILLING PERMIT NO. 95-98-N-58
Other IDWR No. D3832

2. OWNER:
Name Mr. Dick Snyder
Address PO Box 2969
City Hayden State ID Zip 83835

3. LOCATION OF WELL by legal description:
Sketch map location must agree with written location.



Twp. 52 North ☒ or South ☐
Rge. 4 East ☐ or West ☒
Sec. 36, SE (10 acres) 1/4 NE (40 acres) 1/4 SW (160 acres) 1/4
Gov't Lot – County Kootenai
Lat: – : – : – Long: – : – : –
Address of Well Site 14450 North Government Way City Hayden
(Give at least name of road + Distance to Road or Landmark)

Lt. – Blk. – Sub. Name –

4. USE:
☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation
☐ Thermal ☐ Injection ☐ Other

5. TYPE OF WORK check all that apply (Replacement etc.)
☒ New Well ☐ Modify ☐ Abandonment ☐ Other

6. DRILL METHOD
☒ Air Rotary ☐ Cable ☐ Mud Rotary ☐ Other

7. SEALING PROCEDURES

SEAL/FILTER PACK Material	From	To	AMOUNT Sacks or Pounds	METHOD
CS Granular	0'	18½'	400lbs	Dump From Surface

Was drive shoe used? ☒ Y ☐ N Shoe Depth(s) 18½'
Was drive shoe seal tested? ☐Y ☒N How?

8. CASING/LINER:

Diameter	From	To	Gauge	Material	Casing	Liner	Welded	Threaded
6"	+1½'	18½'	.250	CS	☒	☐	☒	☐
					☐	☐	☐	☐
					☐	☐	☐	☐

Length of Headpipe _____ Length of Tailpipe _____

9. PERFORATIONS/SCREENS
☐ Perforations Method
☐ Screens Screen Type

From	To	Slot Size	Number	Diameter	Material	Casing	Liner
						☐	☐
						☐	☐
						☐	☐

10. STATIC WATER LEVEL OR ARTESIAN PRESSURE:
15 ft. below ground Artesian pressure N.A. lb.
Depth flow encountered N.A. ft. Describe access port or control devices: N.A.

52N 4W 36 SE NE SW

11. WELL TESTS:
☐ Pump ☐ Bailer ☒Air ☐ Flowing Artesian

Yield gal./min.	Drawdown	Pumping Level	Time
60	N.D.	23'	½ hr

Water Temp. N.D. Bottom hole temp. N.D.
Water Quality test or comments:
Depth first Water Encountered 12'

12. LITHOLOGIC LOG: (Describe repairs or abandonment)

Bore Dia.	From	To	Remarks: Lithology, Water Quality & Temperature	Water Y	Water N
10"	0'	5'	Overburden		X
10"	5'	10½'	Coarse Sand		X
10"	10½'	12'	Soft Basalt		X
10"	12'	17'	Large Gravel	X	
10"	17'	18½'	Soft Basalt		X
6"	18½'	24'	Soft Basalt	X	

Completed Depth 24' (Measurable)
Date: Started 5/11/98 Completed 5/11/98

13. DRILLER'S CERTIFICATION
I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Firm Name Tacoma Pump & Drilling Firm No. 423
Firm Official [signature] Date 5/11/98
and
Supervisor or Operator _____ Date _____
(Sign once if Firm Official & Operator)

FORWARD WHITE COPY TO WATER RESOURCES