

DRILLER'S REPORT

Use Typewriter or Ballpoint Pen

097139

Office Use Only

 Inspected by _____
 Twp _____ Rge _____ Sec _____
 1/4 1/4 1/4
 Lat: _____ Long: _____

1. DRILLING PERMIT NO

95-96-N-050-000

er IDWR

2. OWNER

Well Number:

Name EVERETT, BRETT


395

Address 202 RIVERWOOD CT

City POST FALLS State ID Zip 83854

3. LOCATION OF WELL by legal description

sketch map location must agree with written location

Twp. 51 ☒ North or ☐ SouthRge. 06 ☐ East or ☒ West

Sec. 01 1/4 SE 1/4 SE 1/4

Gov't Lot _____ County KOOTENAI

Lat: _____ Long: _____

Address of Well Site 8720 N HAUSER LK R

City HAUSER LAK

(Give at least name of road + Distance to Road or Landmark)

Lt. _____ Blk. _____ Sub. Name _____

4. USE:

☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation
☐ Thermal ☐ Injection ☐ Other _____

5. TYPE OF WORK check all that apply (Replacement, etc.)

☒ New Well ☐ Modify ☐ Abandonment ☐ Other _____

DRILL METHOD

☒ Air Rotary ☐ Cable ☐ Mud Rotary ☐ Other _____

7. SEALING PROCEDURES

SEAL/FILTER PACK			AMOUNT	METHOD
Material	From	To	Sacks or Pounds	
BENTONITE	0	18	5 BAGS	DRY

Was drive shoe used? ☐ Y ☐ N Shoe Depth(s) _____Was drive shoe seal tested? ☐ Y ☐ N How? _____

8. CASING/LINER:

Diameter	From	To	Gauge	Material	Casing	Liner	Welded	Threaded
4	-8	460	.160	PSI PVC	☐	☒	☐	☐
6	+1.5	18.5	.250	STEEL	☒	☐	☒	☐
0					☐	☐	☐	☐

Length of Headpipe _____ Length of Tailpipe _____

9. PERFORATIONS/SCREENS

☒ Perforations Method SKILLSAW

☐ Screens Screen Type _____

From	To	Slot Size	Number	Diameter	Material	Casing	Liner
400	420	1/8X4	80	4	PVC	☐	☒
440	460	1/8X4	80	4	PVC	☐	☒

10. STATIC WATER LEVEL OR ARTESIAN PRESSURE:

160 ft. below ground Artesian pressure _____ lb.

Depth flow encountered _____ ft. Describe access port or control devices: _____

11. WELL TESTS:

☐ Pump ☐ Bailer ☒ Air ☐ Flowing Artesian

Yield gal./min.	Drawdown	Pumping Level	Time
10			

Water Temp. _____ Bottom Hole Temp _____

Water Quality test or comments: _____

Depth first Water encountered _____

12. LITHOLOGIC LOG:(Describe repairs or abandonment)

Bore Diam	From	To	Remarks: Lithology, Water Quality, Temperature	Water	
				Y	N
8	0	4	Topsoil	☐	☒
8	4	18	Granite Decomposed Brown	☐	☒
6	18	26	Granite White & Brown Medium	☐	☒
6	26	52	Granite Quartz W/Brown	☐	☒
6	52	108	Granite Brown & White Medium	☐	☒
6	108	154	Granite Copper & Black White Mediu	☐	☒
6	154	158	Granite Green & Black White W/Wate	☒	☐
6	158	164	Granite Black & Copper Medium	☐	☒
6	164	176	Granite White & Black hard	☐	☒
6	176	430	Granite Black & White Copper Mediu	☐	☒
6	430	435	Granite White & Green W/Water 7 GP	☒	☐
6	435	460	Granite Black & White Copper Mediu	☐	☒
	0	0	1 Bolt on Cap	☐	☐
	0	0	1 4x6 Formation Packer set @ 108'	☐	☐
	0	0	Granite/Shale	☐	☐

Completed Depth 460' (Measurable)

Date: Started 05/27/96 Completed 05/28/96

13. DRILLER'S CERTIFICATION

I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Firm Name H2O WellService, Inc. Firm No. 448

Firm Official *Tom Wheeler* Date 5-30-96and Supervisor or Operator *Louie* Date 5-30-96

(Sign Once If Firm Official and Operator)

SESE 1 SIN 6W