


WELL DRILLER'S REPORT

State law requires that this report be filed with the Director, Department of Water Resources
within 30 days after the completion or abandonment of the well.

1. WELL OWNER Name <u>PAUL EGBERT</u> Address <u>HCR 2 Box 145-6 Harrison ID</u> Owner's Permit No. <u>95-90-N-57</u>		7. WATER LEVEL Static water level <u>148'</u> feet below land surface. Flowing? ☐ Yes ☒ No G.P.M. flow _____ Artesian closed-in pressure _____ p.s.i. Controlled by: ☐ Valve ☐ Cap ☐ Plug Temperature _____ °F. Quality _____ Describe artesian or temperature zones below.																																																																																																																							
2. NATURE OF WORK ☒ New well ☐ Deepened ☐ Replacement ☐ Abandoned (describe abandonment procedures such as materials, plug depths, etc. in lithologic log)		8. WELL TEST DATA ☐ Pump ☒ Bailer ☐ Air ☐ Other _____																																																																																																																							
3. PROPOSED USE ☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal ☐ Industrial ☐ Stock ☐ Waste Disposal or Injection ☐ Other _____ (specify type)		<table border="1"><thead><tr><th>Discharge G.P.M.</th><th>Pumping Level</th><th>Hours Pumped</th></tr></thead><tbody><tr><td><u>6</u></td><td><u>253'</u></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr></tbody></table>		Discharge G.P.M.	Pumping Level	Hours Pumped	<u>6</u>	<u>253'</u>																																																																																																																	
Discharge G.P.M.	Pumping Level	Hours Pumped																																																																																																																							
<u>6</u>	<u>253'</u>																																																																																																																								
4. METHOD DRILLED ☐ Rotary ☐ Air ☐ Hydraulic ☐ Reverse rotary ☒ Cable ☐ Dug ☐ Other _____		9. LITHOLOGIC LOG <table border="1"><thead><tr><th rowspan="2">Bore Diam.</th><th colspan="2">Depth</th><th rowspan="2">Material</th><th colspan="2">Water</th></tr><tr><th>From</th><th>To</th><th>Yes</th><th>No</th></tr></thead><tbody><tr><td>8"</td><td>0</td><td>3'</td><td>CLAY + SILT</td><td></td><td>X</td></tr><tr><td>"</td><td>3</td><td>17'</td><td>BROKEN BASALT</td><td></td><td>X</td></tr><tr><td>"</td><td>17</td><td>28'</td><td>BROKEN BASALT + CLAY</td><td></td><td>X</td></tr><tr><td>"</td><td>28</td><td>36'</td><td>CLAY + SAND</td><td></td><td>X</td></tr><tr><td>"</td><td>36</td><td>54'</td><td>BROKEN BASALT</td><td></td><td>X</td></tr><tr><td>"</td><td>54</td><td>67'</td><td>CLAY + SAND</td><td></td><td>X</td></tr><tr><td>"</td><td>67</td><td>71'</td><td>HARD BASALT</td><td></td><td>X</td></tr><tr><td>"</td><td>71</td><td>79'</td><td>BROKEN BASALT + CLAY</td><td></td><td>X</td></tr><tr><td>"</td><td>79</td><td>135'</td><td>CLAY</td><td></td><td>X</td></tr><tr><td>"</td><td>135</td><td>147'</td><td>SILT + FINE SAND</td><td></td><td>X</td></tr><tr><td>"</td><td>147</td><td>151'</td><td>SILT + FINE SAND</td><td>X</td><td></td></tr><tr><td>"</td><td>151</td><td>160'</td><td>SILT, FINE SAND + CLAY</td><td>X</td><td></td></tr><tr><td>"</td><td>160</td><td>173'</td><td>CLAY + SILT</td><td></td><td>X</td></tr><tr><td>"</td><td>173</td><td>215'</td><td>HARD BASALT</td><td></td><td>X</td></tr><tr><td>"</td><td>215</td><td>217'</td><td>HARD BASALT 2 GPM.</td><td>X</td><td></td></tr><tr><td>"</td><td>217</td><td>225'</td><td>HARD BASALT 2 GPM.</td><td>X</td><td></td></tr><tr><td>"</td><td>225</td><td>240'</td><td>HARD BASALT</td><td></td><td>X</td></tr><tr><td>"</td><td>240</td><td>250'</td><td>HARD BASALT 2 GPM.</td><td>X</td><td></td></tr></tbody></table>		Bore Diam.	Depth		Material	Water		From	To	Yes	No	8"	0	3'	CLAY + SILT		X	"	3	17'	BROKEN BASALT		X	"	17	28'	BROKEN BASALT + CLAY		X	"	28	36'	CLAY + SAND		X	"	36	54'	BROKEN BASALT		X	"	54	67'	CLAY + SAND		X	"	67	71'	HARD BASALT		X	"	71	79'	BROKEN BASALT + CLAY		X	"	79	135'	CLAY		X	"	135	147'	SILT + FINE SAND		X	"	147	151'	SILT + FINE SAND	X		"	151	160'	SILT, FINE SAND + CLAY	X		"	160	173'	CLAY + SILT		X	"	173	215'	HARD BASALT		X	"	215	217'	HARD BASALT 2 GPM.	X		"	217	225'	HARD BASALT 2 GPM.	X		"	225	240'	HARD BASALT		X	"	240	250'	HARD BASALT 2 GPM.	X	
Bore Diam.	Depth		Material		Water																																																																																																																				
	From	To		Yes	No																																																																																																																				
8"	0	3'	CLAY + SILT		X																																																																																																																				
"	3	17'	BROKEN BASALT		X																																																																																																																				
"	17	28'	BROKEN BASALT + CLAY		X																																																																																																																				
"	28	36'	CLAY + SAND		X																																																																																																																				
"	36	54'	BROKEN BASALT		X																																																																																																																				
"	54	67'	CLAY + SAND		X																																																																																																																				
"	67	71'	HARD BASALT		X																																																																																																																				
"	71	79'	BROKEN BASALT + CLAY		X																																																																																																																				
"	79	135'	CLAY		X																																																																																																																				
"	135	147'	SILT + FINE SAND		X																																																																																																																				
"	147	151'	SILT + FINE SAND	X																																																																																																																					
"	151	160'	SILT, FINE SAND + CLAY	X																																																																																																																					
"	160	173'	CLAY + SILT		X																																																																																																																				
"	173	215'	HARD BASALT		X																																																																																																																				
"	215	217'	HARD BASALT 2 GPM.	X																																																																																																																					
"	217	225'	HARD BASALT 2 GPM.	X																																																																																																																					
"	225	240'	HARD BASALT		X																																																																																																																				
"	240	250'	HARD BASALT 2 GPM.	X																																																																																																																					
5. WELL CONSTRUCTION Casing schedule: ☒ Steel ☐ Concrete ☐ Other _____ Thickness _____ inches Diameter _____ inches From _____ feet To _____ feet _____ inches _____ inches _____ feet _____ feet _____ inches _____ inches _____ feet _____ feet Was casing drive shoe used? ☒ Yes ☐ No Was a packer or seal used? ☐ Yes ☒ No Perforated? ☐ Yes ☒ No How perforated? ☐ Factory ☐ Knife ☐ Torch Size of perforation _____ inches by _____ inches Number _____ From _____ To _____ _____ perforations _____ feet _____ feet _____ perforations _____ feet _____ feet _____ perforations _____ feet _____ feet Well screen installed? ☐ Yes ☒ No Manufacturer's name _____ Type _____ Model No. _____ Diameter _____ Slot size _____ Set from _____ feet to _____ feet Diameter _____ Slot size _____ Set from _____ feet to _____ feet Gravel packed? ☐ Yes ☒ No ☐ Size of gravel _____ Placed from _____ feet to _____ feet Surface seal depth <u>20'</u> Material used in seal: ☐ Cement grout ☒ Bentonite ☒ Puddling clay ☐ Sealing procedure used: ☐ Slurry pit ☒ Temp. surface casing ☐ Overbore to seal depth Method of joining casing: ☐ Threaded ☒ Welded ☐ Solvent Weld _____ ☐ Cemented between strata Describe access port <u>1" PLUG IN WELL CAP</u>		RECEIVED AUG 10 1990 NORTHERN REGION IDWR SCANNED MAR 01 2018																																																																																																																							
6. LOCATION OF WELL Sketch map location must agree with written location.  Subdivision <u>NW 21 1991</u> Lot No. <u>7</u> Block No. _____ County <u>KOOTENAI</u> <u>S.W. 1/4 A.E. 1/4 Sec. 17, T. 49 N., R. 3 E.W.</u>		10. Work started <u>July 2, 1990</u> finished <u>July 26, 1990</u>																																																																																																																							
11. DRILLERS CERTIFICATION I/We certify that all minimum well construction standards were complied with at the time the rig was removed. Firm Name <u>FLANIGAN & FLANIGAN</u> Firm No. <u>433</u> Address <u>PO Box 320 Park Dr. ID</u> Date <u>July 26, 1990</u> Signed by (Firm Official) <u>James H. Flanigan</u> and (Operator) <u>James H. Flanigan</u>																																																																																																																									