

RECEIVED

Form 238-7

DEC 23 1997



IDAHO DEPARTMENT OF WATER RESOURCES

WELL DRILLER'S REPORT 097129

Use Typewriter or Ballpoint Pen

NORTHERN REGION

IDWR

1. DRILLING PERMIT NO. 95-97-N-136

Other IDWR No. D3249

2. OWNER:

Name Dick & Keita Cooper

Address 1105 Prairie Lane

City Post Falls State ID Zip 83854

3. LOCATION OF WELL by legal description:

Sketch map location must agree with written location.

N		Twp. <u>51</u>		North ☒ or South ☐	
E		Rge. <u>5</u>		East ☐ or West ☒	
S		Sec. <u>9</u>		1/4 SW 1/4 SW 1/4 NW 1/4	
W		Gov't Lot		County <u>KOOTENAI</u>	
		Lat:		Long:	

Address of Well Site Howell Road

(Give at least name of road + Distance to Road or Landmark)

Lt. 1 Blk. N/A Sub. Name K.C. Acres

4. USE:

- ☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation
☐ Thermal ☐ Injection ☐ Other

5. TYPE OF WORK check all that apply (Replacement etc.)

- ☒ New Well ☐ Modify ☐ Abandonment ☐ Other

6. DRILL METHOD

- ☒ Air Rotary ☐ Cable ☐ Mud Rotary ☐ Other

7. SEALING PROCEDURES

SEAL/FILTER PACK			AMOUNT		METHOD
Material	From	To	Sacks or Pounds		
CS Granular	0'	20'	500lbs		Dump From Surface

Was drive shoe used? ☒ Y ☐ N Shoe Depth(s) 55'

Was drive shoe seal tested? ☐ Y ☒ N How?

8. CASING/LINER:

Diameter	From	To	Gauge	Material	Casing	Liner	Welded	Threaded
6"	+2'	55'	.250	C.S.	☒	☐	☒	☐
4"	50'	250'	.160	PVC	☐	☒	☐	☐
			PST		☐	☐	☐	☐

Length of Headpipe Length of Tailpipe

9. PERFORATIONS/SCREENS

- ☒ Perforations Method Hand Drill
☐ Screens Screen Type

From	To	Slot Size	Number	Diameter	Material	Casing	Liner
230'	250'	N/A	40	1/2"	PVC	☐	☒

10. STATIC WATER LEVEL OR ARTESIAN PRESSURE:

50 ft. below ground Artesian pressure N/A lb.

Depth flow encountered 230.0 ft. Describe access port or control devices: N/A

11. WELL TESTS:

- ☐ Pump ☐ Bailor ☒ Air ☐ Flowing Artesian

Yield gal./min.	Drawdown	Pumping Level	Time
1gpm	N.D.	245.0'	1 1/2 hrs.

Water Temp. Bottom hole temp.

Water Quality test or comments:

Depth first Water Encountered 230'

12. LITHOLOGIC LOG: (Describe repairs or abandonment)

Bore Dia.	From	To	Remarks: Lithology, Water Quality & Temperature	Y	N
10"	0'	2'	Over Burden		X
10"	2'	11'	Small Gravel/Fine Sand		X
10"	11'	19'	Coarse Gravel/Fine Sand		X
6"	19'	27'	Coarse Gravel/Fine Sand		X
6"	27'	45'	Fine Sand		X
6"	45'	53'	Coarse Gravel/Fine Sand		X
6"	53'	55'	Soft Granite		X
6"	55'	225'	Hard Salt & Pepper Granite		X
6"	225'	240'	Soft Granite	X	
6"	240'	250'	Hard Salt & Pepper Granite		X

Completed Depth 250.0' (Measurable)
 Date: Started 11/11/97 Completed 11/21/97

13. DRILLER'S CERTIFICATION

I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Firm Name Tacona Pump & Drilling Firm No. 423

Firm Official [Signature] Date 12/19/97

and Supervisor or Operator Date 12/19/97

(Sign once if Firm Official & Operator)

SWSWNW 9 SIN 5W

IDAHO DEPARTMENT OF WATER RESOURCES