

Identify from:  Parcels

 Parcels

 BROWN, LONNIE M



Location: 2,282,302.204 1,764,803.524 Meters

Field	Value
ACRES	14
ADDRESS1	6290 HIGHWAY 95
ADDRESS2	
CITY	POTLATCH
COUNTY	Latah
ID	11254497
LEGAL1	14.78 AC OF TAX #6501 SESW &
LEGAL2	SWSE LESS S 130'
LEGAL3	20 43 4
LEGAL4	
LEGAL5	
LEGAL6	
OWNER	BROWN, LONNIE M
P_ADDRESS	6290 HWY 95 N
P_ZIPCODE	83855
PIN	RP43N04W208510
SOURCE	<null>
STATE	ID
SUB_NAME	
UPDATED	6/3/2019
YEAR_BUILT	2008
ZIPCODE	83855

Identified 1 feature



IDAHO DEPARTMENT OF WATER RESOURCES
WELL DRILLER'S REPORT

Office Use Only			
Well ID No.			
Inspected by			
Twp	Rge	Sec	
1/4	1/4	1/4	
Lat:	:	Long:	:

1. WELL TAG NO. D 0040540
DRILLING PERMIT NO. 837682
Water Right or Injection Well No. _____

2. OWNER:

Name Larry Brown
Address 3459 HWY 6
City Princeton State ID Zip 83857

3. LOCATION OF WELL by legal description:

You must provide address or Lot, Blk, Sub. or Directions to well.

Twp. 43 North ☒ or South ☐
Rge. 4 East ☐ or West ☒
Sec. 20 1/4 SW 1/4 SE 1/4
Gov't Lot _____
County Latah
Lat: _____ Long: _____
Address of Well Site Benaiah County Line
HWY 95 City Patlach
(Give at least name of road + Distance to Road or Landmark)
Lt. _____ Blk. _____ Sub. Name _____

4. USE:

☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation
☐ Thermal ☐ Injection ☐ Other _____

5. TYPE OF WORK check all that apply

☒ New Well ☐ Modify ☐ Abandonment ☐ Other _____ (Replacement etc.)

6. DRILL METHOD:

☒ Air Rotary ☐ Cable ☐ Mud Rotary ☐ Other _____

7. SEALING PROCEDURES

Seal Material	From	To	Weight / Volume	Seal Placement Method
<u>Bentonite</u>	<u>0</u>	<u>30</u>	<u>4 lbs</u>	<u>Dry</u>

Was drive shoe used? ☒ N ☐ Shoe Depth(s) 59'

Was drive shoe seal tested? ☒ N ☐ How? dir

8. CASING/LINER:

Diameter	From	To	Gauge	Material	Casing	Liner	Welded	Threaded
<u>6" + 2</u>	<u>0</u>	<u>1250</u>	<u>std</u>	<u>steel</u>	☒	☐	☒	☐
<u>4 1/2 - 43</u>	<u>403</u>	<u>160</u>	<u>PVC</u>	<u>PVC</u>	☐	☒	☐	☐

Length of Headpipe _____ Length of Tailpipe _____

Packer ☐ Y ☒ N Type _____

9. PERFORATIONS/SCREENS PACKER TYPE

Perforation Method scr cut

Screen Type & Method of Installation

From	To	Slot Size	Number	Diameter	Material	Casing	Liner
<u>360</u>	<u>400</u>	<u>8X3</u>	<u>100</u>	<u>4 1/2</u>	<u>PVC</u>	☐	☒

10. FILTER PACK

Filter Material	From	To	Weight / Volume	Placement Method

11. STATIC WATER LEVEL OR ARTESIAN PRESSURE:

3 ft. below ground Artesian pressure _____ lb.

Depth flow encountered _____ ft. Describe access port or control devices: _____

Stop & well

+3N 4W 20

12. WELL TESTS:

☐ Pump	☐ Bailer	☒ Air	☐ Flowing Artesian
Yield gal./min.	Drawdown	Pumping Level	Time
<u>13 gpm</u>			<u>1.5</u>

Water Temp. 54° Bottom hole temp. 54°

Water Quality test or comments: Good

13. LITHOLOGIC LOG: (Describe repairs or abandonment)

Bore Dia.	From	To	Remarks: Lithology, Water Quality & Temperature	Y	N
<u>10</u>	<u>0</u>	<u>2</u>	<u>dirt</u>		
	<u>2</u>	<u>17</u>	<u>clay</u>		
	<u>17</u>	<u>31</u>	<u>soft grout</u>		
	<u>31</u>	<u>38</u>	<u>clay</u>		
	<u>38</u>	<u>46</u>	<u>soft grout</u>		
	<u>46</u>	<u>53</u>	<u>clay</u>		
	<u>53</u>	<u>60</u>	<u>soft grout</u>		
	<u>60</u>	<u>275</u>	<u>red grout</u>		
	<u>275</u>	<u>325</u>	<u>soft wood with</u>		
			<u>some water</u>		
	<u>325</u>	<u>353</u>	<u>hard grout</u>		
	<u>353</u>	<u>410</u>	<u>after 13 gpm</u>		

RECEIVED
AUG 29 2005
IDWR/North

Completed Depth 400 ft (Measurable)

Date: Started 8/10/05 Completed 8/12/05

14. DRILLER'S CERTIFICATION

I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Company Name V. H. H. Drilling Firm No. 125

Principal Driller Wm. H. H. Date 8/21/05

Driller or Operator II _____ Date _____

Operator I _____ Date _____

Principal Driller and Rig Operator Required.
Operator I must have signature of Driller/Operator II.