

Licensing Review For Permit No: 96-8563

Date: 05/22/15

A. GENERAL INFORMATION

1. Field Exam dated 1213//99

2. Current Owner: Name: USFS

Owner of Record Correct? X Y NAddress of Record Correct? X Y N

If No: Address

3. Beneficial Use Fees have been paid: X Y N Receipt No: NO133834. SOURCE TRIBUTARY

Grouse Creek

Pack River

Method of Determination: Field Exam dated 12/13/99

Change in Source: Y X N**B. OVERLAP REVIEW**1. Other water rights with the same place of use: X NO Overlap

Water Right No.	Source	Purpose of Use	Basis

Comments:

2. Other water rights with the same point of diversion: X NO Overlap

Water Right No.	Source	Purpose of Use	Basis

Comments: 96-2136 is in same QQ as POD of 96-8563. Field Examiner did not note any overlapping POD. Ditch for 96-2136 travels south to POU, perhaps along road. 96-8563 appears to be single pump diversion from creek.

- No overlap noted.

C. DIVERSION AND DELIVERY SYSTEM1. LOCATION OF POINT(S) OF DIVERSION:

Source	Govt. Lot	¼	¼	¼	Sec.	Twp.	Rge.		County
Grouse Creek			SW	NW	30	59N	01E	B.M.	Bonner

Method of Determination:

Per Field Exam dated 12/13/99

Change in POD? Y X N Amendment Required? Y X N

2. **PLACE OF USE:** Use: Irrigation & Irrigation from Storage

TWP	RGE	Sec	NE				NW				SW				SE				Total s
			N E	NW	SW	S E	NE	N W	SW	SE	NE	NW	S W	SE	N E	N W	S W	SE	
59N	01E	30		0.2	6.1		6.9		0.5	21.5	11.1	11.3	2.5	7.7		3.1	1.6		72.5
		Lot #							2			3	4						

Method of Determination: Map in Field Exam dated 12/13/99

Although Section C.2. of Field Exam indicates only 66.5 acres irrigated, the map of the field exam indicates 72.5 acres. The field examiner appears to have incorrectly added the acres in the NESW and SESW and omitted the acres in the SWSW as indicated on the map included in the field exam.

The acres derived using current GIS and PLS shows a shift in the acres per QQ from the field exam. This is due to the PLS grid aligning differently than the grid drawn by the field examiner.

Use: Irrigation Storage

TWP	RGE	Sec	NE				NW				SW				SE				Totals
			NE	NW	SW	SE	NE	NW	SW	SE	NE	NW	SW	SE	NE	NW	SW	SE	
59N	01E	30								X	X			X					
		Lot #							2			3	4						

Method of Determination: Field Exam dated 12/13/99

An amendment is needed as more QQ have been found to be irrigated than those permitted for.

Change in POU? X Y N Amendment Required? X Y N Delivery System Diagram Attached (required). Indicate all major components and distances between components.

Indicate weir size/pipe as applicable.

 Aerial Photo Attached (required for irrigation of 10+ acres). Photo of Diversion and System Attached

4. Well or Diversion Identification No.*	Motor Make	Hp	Motor Serial No.	Pump Make	Pump Serial No. or Discharge Size

*Code to correspond with No. on map and aerial photo

D. FLOW MEASUREMENTS

1.Measurement Equipment	Type	Make	Model No.	Serial No.	Size	Calib. Date

2. Measurements: See calculations on Field Exam dated 12/13/99

E. FLOW CALCULATIONS Additional Computation Sheets Attached**Irrigation:** System Flow meter = 1.0 cfs. Measured Method: See calculations on Field Exam dated 12/13/99, section F**Diversion to Storage:** Q of Field Exam dated 12/13/99, section F Head to PSI calculation incorrect.

250 ft. head lift from pump to pond. Convert to PSI = $250/2.31 = 108.225$ psi. Assume 15 PSI for open discharge from pipe into pond. Total PSI against pump = $(108 + 15) = 123$ PSI. Assume standard 10 ft. lift from creek to pump. 60 hp. Pump per

field exam dated 12/13/99 at creek.

$$Q = (8.8 * 60 * 0.7) / (10 + (123 * 2.31)) = 1.26 \text{ cfs}$$

Permit allowed = 1.00 cfs irrigation and diversion to storage

License recommend for 1.00 cfs. Irrigation and diversion to storage

F. VOLUME CALCULATIONS

1. Volume Calculations for Irrigation:

$$V_{I.R.} = (\text{Acres Irrigated}) \times (\text{Irrigation Requirement}) = 72.5 \times 3 = 217.5$$

$$V_{D.R.} = [\text{Diversion Rate (cfs)}] \times (\text{Days in Irrigation season}) \times 1.9835 = 1 \times 90 \times 1.9835 = 178.5 \text{ afa per field exam}$$

$$V = \text{Smaller of } V_{I.R.} \text{ and } V_{D.R.} =$$

- License recommend N/A Irr. Exempt I.C. 37.03.02

Volume calculations differ from field examiner: Although Section C.2. of Field Exam indicates only 66.5 acres irrigated, the map of the field exam indicates 72.5 acres. The field examiner appears to have incorrectly added the acres in the NESW and SESW and omitted the acres in the SWSW as indicated on the map included in the field exam.

2. Volume Calculations for Other Uses:

Per Field Exam dated 12/13/99, (7 Ac area at 20 ft deep with 0.4 slope) total capacity 56 afa. 7 AF also consistent with GIS acres.

Pond Spreadsheet – estimated evaporation loss = 10.2 af. Capacity + evaporation loss > 57 afa

- Permit limited to 57.0 afa storage
- License recommend for 57.0 afa storage

G. PURPOSE OF USE

Irrigation _____ N # Stock _____ Domestic # of Homes _____

Other: Diversion to Storage, Irrigation from Storage

Change in Purpose of Use? ____Y ____X ____N

If Yes: From Use _____ To Use _____ Amount _____ CFS _____ AFA _____

Method of Determination: Field Exam dated 12/13/99

H. NARRATIVE/REMARKS/COMMENTS

Season of Use: 04/01 to 10/31 Headgate: 3 Cons. Use: 2 MSF Grouse Creek 96-7980

No Water District or Ground Water District

Have conditions of permit approval been met? ____X____ Yes ____ No

I. RECOMMENDATIONS

1. Recommended Amounts

<u>BENEFICIAL USE</u>	<u>PERIOD OF USE</u>	<u>DIVERSION RATE</u>	<u>ANNUAL VOLUME</u>
Irrigation	04/01 to 06/30	1.00 CFS	N/A AFA
Irrigation From Storage	04/01 to 06/30	N/A CFS	57.0 AFA
Irrigation Storage	04/01 to 09/01	N/A CFS	57.0 AFA
Diversion to Storage	04/01 to 06/30	1.00 CFS	N/A AFA
Irr. Exempt I.C. 37.03.02			
<u>Totals:</u>		1.00 CFS	57.0 AFA

2. Recommended Amendments

☐ Change P.D. as reflected above ☐ Add P.D. as reflected above ☒ None

☒ Change P.U. as reflected above ☐ Add P.U. as reflected above ☐ None

Other:

J. AUTHENTICATION

Field Examiner's Name *Dorelle Turner* Date 07/09/15

Reviewer *Daniel A. Moran* Date 7-10-15


96-8563



0 125 250 500 750 1,000 Feet

D. Favreau 05/21/15

NAPP 1998



96-03-03-03-03

48.6
6.3
6.2
5.4
6.0

72.5 total
AC

9
16.5
5.3 →
2.0
15.0
0.8

48.6


5.5
0.8

6.3 5.6
 0.6

6.2

4.1
1.1
0.2

5.4
← 6AC



SW
NW

NE
NW

NW
NE

SW
NE

SE
NW

NW
SW

NE
SW

NW
SE

SE
SW

SW
SW

Total Storage Calculations

FILE NUMBER	96-8563
REVIEWER	D. Favreau
DATE	6/30/2015

This spreadsheet has been designed by Idaho Department of Water Resources to estimate the total seepage, evaporation and fill capacity required for a pond.

User Input
Calculated value
Formula Explanations

Surface Area (AC.)	7	"Surface Area" is automatically carried over from the "Seepage Loss" sheet.
Average Pond Depth (FT.)	8	"Average Pond Depth" depicts the actual depth of the pond either measured or estimated. Note: If you know the maximum depth and not the average depth, the Field Examiner's Handbook suggests multiplying the maximum depth by 0.4 to get the average depth, or you can use any method that seems reasonable to attain average depth.
Pond Capacity (AF)	56	Pond Capacity is calculated by multiplying the Pond Surface Area by the Average Pond Depth. If you know the capacity, divide the capacity by surface area and enter the average pond depth in the space above. Note: If pond capacity is determined using a method shown on the "Pond Capacity" sheet, the user may need to modify the value of "Pond Capacity" (cell B9) manually. Note that if the value is modified manually, the formula will be altered for future use.

Multiple Fill Volume Above Initial Fill to Fulfill From Storage Needs- "Multiple Fills" (AF)	0	The "Multiple Fill Volume Above Initial Fill" is the acre-feet of water required to meet a from storage component if the from storage component exceeds a one time fill. This section should not include the amount of water needed to fill the pond initially or the amount of water needed to maintain the pond level due to evaporation or seepage. For example: If a pond has a capacity of 5 acre feet and 2.5 acre feet of seepage and evaporation, but the pond is used for irrigation that requires 10 acre feet of from storage for the irrigation use, then you would insert 5 acre feet into this location (10 acre feet needed - 5 acre feet from the initial fill = 5 acre feet of additional storage needed). Note: You must have a "From Storage" component exceeding the initial fill on the permit to include a volume in this space.
Estimated Seepage Loss (AF)	511.0	The "Estimated Seepage Loss" is automatically carried over from the "Seepage Loss" sheet.
Estimated Evaporation Loss (AF)	10.2	The "Estimated Evaporation Loss" is automatically carried over from the "Evaporation Loss" sheet.
Total Volume Required (AF)	577.2	The "Total Volume Required" is calculated by adding the Pond Capacity, Multiple Fills, Seepage Loss, and Evaporation Loss amounts to determine the total amount of storage required.

Flow Rate Into Pond (CFS)	1.00	The "Flow Rate into Pond" depicts the actual flow, either measured or estimated, into the pond. For offstream facilities, this will be equivalent to "diversion to storage" rate.
Highest Daily Evaporation Rate From Evaporation Tab. (mm/Day)	4.06	This number is carried over from the "Evaporation Loss" sheet. It is the highest recorded number in the "Precipitation Deficit Table".
Required Daily Maintenance Volume (AF/Day)	1.49	"Required Daily Maintenance Volume" is the maximum volume of water needed on any given day during the year to maintain pond volume. It is calculated by adding the highest daily evaporation loss to the average daily seepage loss in acre feet. The average daily seepage loss is calculated by dividing the "Estimated Seepage Loss" by 365 days. This is acceptable, since the seepage rate shouldn't vary throughout the season unless the pond completely freezes over during the winter months. The highest daily evaporation loss is calculated by dividing the Highest Daily Evaporation Rate by the 304.8 conversion factor and multiplying this number by the pond surface area to attain a combined daily acre feet requirement.
Minimum Maintenance Flow (CFS)	0.75	The "Minimum Maintenance Flow" is the minimum amount of flow required to maintain the level of the pond. This number is determined by dividing the "Maximum Required Daily Maintenance Volume" by 1.9835. This flow can be used to determine if the flow rate into the pond is adequate to maintain the pond level.
Days Required to Fill the Pond	114	The "Days Required to Fill the Pond" is calculated by dividing the "Pond Capacity" by the "Flow Rate" minus "Minimum Maintenance Flow" multiplied by 1.9835. This section will assist you in determining if the flow rate being diverted to the pond is adequate to fill the pond while maintaining the pond level. The length of time to fill the pond will help determine if the flow rate is adequate for the size of pond being proposed. If this number is approximately 6 months (180 days) or more, the reviewer should have a discussion with the applicant to make sure he/she understands that it will take a significant length of time to fill the pond.
Days Required to Fill the Pond at 13,000 Gallons per Day	-39	Some water users may want to fill a pond under the 13,000 gallons per day domestic exemption. The "Days Required to Fill the Pond at 13,000 Gallons per Day" is calculated by converting the "Pond Capacity" and the "Required Daily Maintenance Volume" to gallons. The "Pond Capacity" is then divided by 13,000 gallons minus the "Required Daily Maintenance Volume" in gallons to determine the number of days to fill pond. If this number is approximately 6 months (180 days) or more, the reviewer should have a discussion with the applicant to make sure he/she understands that it will take a significant length of time to fill the pond. Negative values indicate that the supply of 13,000 gallons per day is not enough volume to overcome the required daily maintenance volume; the pond will never fill.

ET_{Idaho} 2012 -- Evapotranspiration and Consumptive Irrigation Water Requirements for Idaho

Please send suggestions for improving this site to robison at kimberly dot uidaho dot edu Copyright 2012, University of Idaho.

Sandpoint KSPT (NWS -- 108137)

Statistics based on thirty year normal spans 1973 to 2007 years

For a different land cover or crop click on the above link.

You can highlight this table and copy via the clipboard to a Microsoft Excel or OpenOffice spreadsheet to plot or otherwise work with this data.

Open water - small stock ponds															
Precipitation Deficit (Click here for a graph)															
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Growing Season ^a	Non Growing Season ^b	Annual
Mean ^j	mm/day												mm		
Monthly ^c	-3.28	-2.14	-0.65	0.96	1.44	2.31	4.06	3.58	2.13	-0.25	-3.90	-3.70	21	0	21
15-Day Moving Average ^d	-3.36	-2.44	-0.70	0.93	1.50	2.18	4.01	3.57	1.98	-0.21	-3.91	-3.60			
7-Day Moving Average ^e	-3.32	-2.25	-0.71	0.91	1.48	2.20	4.05	3.58	2.06	-0.20	-3.99	-3.59			
3-Day Moving Average ^f	-3.28	-2.14	-0.66	0.93	1.45	2.25	4.06	3.58	2.11	-0.23	-3.92	-3.67			
Standard Deviation ^k	mm/day												mm		
Monthly ^c	2.54	1.88	1.61	1.04	1.84	1.28	2.27	2.10	1.25	2.08	1.93	2.29	160	0	160
15-Day Moving Average ^d	2.58	2.51	1.70	1.51	2.03	1.97	2.12	1.98	1.79	1.94	2.53	2.35			
7-Day Moving Average ^e	3.49	3.40	2.29	2.36	2.77	2.80	2.42	2.62	2.32	2.57	3.76	3.40			
3-Day Moving Average ^f	4.68	4.39	3.26	3.23	3.82	3.83	3.01	3.35	3.00	3.39	5.44	4.92			
20% Exceedance ^l	mm/day												mm		
Monthly ^c	-2.20	-0.47	0.25	1.82	2.47	3.27	5.05	4.87	3.40	0.76	-2.36	-2.38	144	0	144
15-Day Moving Average ^d	0.07	0.19	1.62	3.03	4.32	4.92	5.89	5.51	4.14	2.08	0.00	0.00			
7-Day Moving Average ^e	0.35	1.03	2.34	3.84	5.55	5.77	6.28	6.03	4.60	2.80	0.78	0.20			
3-Day Moving Average ^f	0.54	1.43	2.90	4.49	5.97	6.56	6.65	6.40	5.14	3.08	1.12	0.36			
80% Exceedance ^m	mm/day												mm		

Evaporation Loss Calculations

This spreadsheet has been designed by Idaho Department of Water Resources to estimate the annual evaporation losses from a pond.

FILE NUMBER	96-8563
REVIEWER	D. Favreau
DATE	6/30/2015

User Input
Calculated value
Formula Explanations

The acronyms used on the Kimberly Research Center website are defined below:
P = Precipitation
ET= Evapotranspiration
P _d = Precipitation deficit
P _d =ET-P

USING THIS SPREADSHEET

Use the link below to access the Kimberly Research Center website. This website provides the Precipitation Deficit for a station most representative of the pond under examination. The Precipitation Deficit is the total amount of free water surface evaporation minus the precipitation for a given area, which gives the total amount of evaporative losses incurred by the pond. There are several weather sites that are used throughout the state. IDWR staff can find the nearest site using Arc Map. The shape file containing the sites can be found at <X:/Spatial/Climate/ETIdahostations.shp>.

Instructions:

1. Use the link below to navigate to ET Idaho 2012.
2. Select the station which is most representative to your pond location.
3. Click Submit Query.
4. Under "Land Covers with Evapotranspiration Estimates," select "Open Water - Shallow Systems (ponds, streams)" or "Open Water - small stock ponds" depending on the pond size.
5. Click the link to "Precipitation Deficit."
6. Reference and copy (ctrl + C) the first subheading "Mean" values.
7. Click the "Paste Values from ET Idaho" button. The table will automatically enter a zero (0) for any negative precipitation deficit values.

Found at: <http://data.kimberly.uidaho.edu/ETIdaho/>

Precipitation Deficit

Station: Twin Falls 2 NNE (NWS -- 109294)

Month	mm/day ¹	Days per month	mm/Month
Jan	-3.28	31	0.00
Feb	-2.14	28	0.00
March	-0.65	31	0.00
April	0.96	30	28.80
May	1.44	31	44.64
June	2.31	30	69.30
July	4.06	31	125.86
August	3.58	31	110.98
September	2.13	30	63.90
October	-0.25	31	0.00
November	-3.90	30	0.00
December	-3.70	31	0.00

PLEASE NOTE: The seasonal average for precipitation deficit should not be used for calculations because precipitation often exceeds evaporation during wetter months of the year. If the pond is kept full, excess precipitation during wetter months does not serve to refill the pond during drier months.

For example, see Sandpoint KSPT (NWS -- 108137), the annual precipitation deficit is -106 mm. However, April through September have positive precipitation deficit values. To properly estimate the annual volume of water necessary to refill a pond due to evaporation losses, the table will automatically enter a zero (0) for each month that the precipitation value is reported as a negative value.

As described above, precipitation offsets evaporation in winter months, so the net effect is that wintertime precipitation deficit is usually zero.

Total mm/year = 443.48

$$((\text{mm/yr}) \div (\text{convert to feet})) \times (\text{Surface area of pond, in acres}) = \text{Evaporation Loss in Acre Feet}$$

(443.48 ÷ 304.8) X 7.00 = 10.2 AFA

Seepage Loss Calculations

This spreadsheet has been designed by Idaho Department of Water Resources to estimate the total annual seepage losses from a pond.

FILE NUMBER	96-8563
REVIEWER	D. Favreau
DATE	6/30/2015

User Input
Calculated value
Formula Explanations

INPUTS

Pond Surface Area (AC.)	7	AC.
-------------------------	---	-----

Pond Surface Area (SQ. FT.)	304920	SQ. FT.
-----------------------------	--------	---------

I used the following method to obtain my Soil Classification information:	NRCS Web Soil Survey	
My Soil Classification is	SM	
Suggested Seepage Rate (FT./DAY)	0.2000	FT./DAY

Formula: (Surface Area X Seepage Rate) X 7.48 = Gallons Per Day Loss
--

Convert to GPD	456160	GPD
----------------	--------	-----

Total Seepage Loss (AFA)	511.0	AFA
--------------------------	-------	-----

Though sand and gravel seepage rates may actually be higher, the maximum allowable rate is 0.2 ft/day, pursuant to Administrative Memo "Seepage Loss Standards for Ponds and Reservoirs."

Suggested Seepage Rates for Different Soil Types:

GW, GP, GM, GC, SW, SP and SM (silty sand, sand silt mixtures and gravel mixtures) = 0.2 ft per day

OL and ML (inorganic silts - very fine sands, silty, or clayey fine sands) = 0.02 ft per day

SC (clayey sands, sand clay mixtures) = 0.007 ft per day

CL (Low to medium plasticity clays) = 0.003 ft per day

MH, OH, PT and CH (high plasticity clays) = 0.0003 ft per day

LINED PONDS (liners can be chemical, fabric, or bentonite) = 0 ft per day

Ponds Intercepting Groundwater (excavated ponds filled by ground water) = 0 ft per day

PLEASE NOTE: The initial basis for the Suggested Seepage Rates in the table above is found on Page 16 of Seepage from Fish Ponds, Bulletin 599, August 1989 Alabama Agricultural experiment Station, Auburn University, Auburn University Alabama. If you don't know the soil type, please refer to the map provided at the NRCS Web Soil Survey (Tab #1), an ArcMap Soil Classification Map (Tab #1.1), or published NRCS Soil Survey (Tab #1.2). Use "0" if the pond fill relies on the water table.

Process	Basin Sequence	Draft	Owner	Source	POD/ POU	NENE	NWNE	SWNE	SENE	NENW	NWNW	SWNW	SENW	NESW	NWSW	SWSW	SESW	NESE	NWSE	SWSE	SESE	Total Acres
Water Right	96-2136	N	CLAUSSEN, JOHN P; ZUELKE, ALICE;	GROUSE CREEK	POD							X										0
Water Permit	96-8563	N	US DEPT OF AGRICULTURE	GROUSE CREEK	POD							X										0
Water Permit	96-8563	N	US DEPT OF AGRICULTURE	GROUSE CREEK	POU		8.0	40.0						35.0	25.0	15.0	30.0				20.0	173

Remove
before
summit
for winds