

## WELL DRILLER'S REPORT

State law requires that this report be filed with the Director, Department of Water Resources  
within 30 days after the completion or abandonment of the well.

## 1. WELL OWNER

Name HARVEY R. CONVERSE  
Address HCP 6 Box 38A Priest River IDA.  
Owner's Permit No. 97-91-N-38

## 7. WATER LEVEL

Static water level 175 feet below land surface.  
Flowing? ☐ Yes ☒ No G.P.M. flow \_\_\_\_\_  
Artesian closed-in pressure \_\_\_\_\_ p.s.i.  
Controlled by: ☐ Valve ☐ Cap ☐ Plug  
Temperature 50 °F. Quality good  
Describe artesian or temperature zones below.

## 2. NATURE OF WORK

- ☒
- New well
- ☐
- Deepened
- ☐
- Replacement
- 
- ☐
- Well diameter increase
- 
- ☐
- Abandoned (describe abandonment procedures such as materials, plug depths, etc. in lithologic log)

## 8. WELL TEST DATA

☐ Pump ☐ Bailer ☒ Air ☐ Other \_\_\_\_\_

Discharge G.P.M. \_\_\_\_\_ Pumping Level \_\_\_\_\_ Hours Pumped \_\_\_\_\_

40+ air test approx 2


## 3. PROPOSED USE

- ☒
- Domestic
- ☐
- Irrigation
- ☐
- Test
- ☐
- Municipal
- 
- ☐
- Industrial
- ☐
- Stock
- ☐
- Waste Disposal or Injection
- 
- ☐
- Other \_\_\_\_\_ (specify type)

## 9. LITHOLOGIC LOG

079903

| Bore<br>Diam. | Depth |     | Material                      | Water |                                     |
|---------------|-------|-----|-------------------------------|-------|-------------------------------------|
|               | From  | To  |                               | Yes   | No                                  |
| 10            | 0     | 4   | gravel - sand                 |       | <input checked="" type="checkbox"/> |
| 10            | 4     | 16  | sand                          |       | <input checked="" type="checkbox"/> |
| 10            | 16    | 20  | sand-gravel w/ clay           |       | <input checked="" type="checkbox"/> |
| 6             | 20    | 30  | sand - gravel                 |       | <input checked="" type="checkbox"/> |
|               | 30    | 55  | sand - trace of gravel        |       | <input checked="" type="checkbox"/> |
|               | 55    | 62  | fine sand                     |       | <input checked="" type="checkbox"/> |
|               | 62    | 73  | sand & lite gravel            |       | <input checked="" type="checkbox"/> |
|               | 73    | 245 | gray clay                     |       | <input checked="" type="checkbox"/> |
|               | 245   | 255 | sand - fine - trace of gravel |       | <input checked="" type="checkbox"/> |
|               | 255   | 265 | sand & gravel                 |       | <input checked="" type="checkbox"/> |
|               | 265   | 273 | sand & gravel                 |       | <input checked="" type="checkbox"/> |
|               | 273   | —   | clay                          |       | <input checked="" type="checkbox"/> |



## 4. METHOD DRILLED

- ☒
- Rotary
- ☒
- Air
- ☐
- Hydraulic
- ☐
- Reverse rotary
- 
- ☐
- Cable
- ☐
- Dug
- ☐
- Other \_\_\_\_\_

## 5. WELL CONSTRUCTION

Casing schedule: ☒ Steel ☐ Concrete ☐ Other \_\_\_\_\_Thickness 2.50 inches Diameter 6 inches + 1.6 feet 265 feet  
\_\_\_\_\_ inches \_\_\_\_\_ inches \_\_\_\_\_ feet \_\_\_\_\_ feet  
\_\_\_\_\_ inches \_\_\_\_\_ inches \_\_\_\_\_ feet \_\_\_\_\_ feet  
\_\_\_\_\_ inches \_\_\_\_\_ inches \_\_\_\_\_ feet \_\_\_\_\_ feetWas casing drive shoe used? ☒ Yes ☐ No  
Was a packer or seal used? ☐ Yes ☒ No  
Perforated? ☐ Yes ☒ No  
How perforated? ☐ Factory ☐ Knife ☐ Torch ☐ Gun  
Size of perforation \_\_\_\_\_ inches by \_\_\_\_\_ inchesNumber \_\_\_\_\_ From \_\_\_\_\_ To \_\_\_\_\_  
\_\_\_\_\_ perforations \_\_\_\_\_ feet \_\_\_\_\_ feet  
\_\_\_\_\_ perforations \_\_\_\_\_ feet \_\_\_\_\_ feet  
\_\_\_\_\_ perforations \_\_\_\_\_ feet \_\_\_\_\_ feetWell screen installed? ☐ Yes ☒ No

Manufacturer's name \_\_\_\_\_

Type \_\_\_\_\_ Model No. \_\_\_\_\_

Diameter \_\_\_\_\_ Slot size \_\_\_\_\_ Set from \_\_\_\_\_ feet to \_\_\_\_\_ feet

Diameter \_\_\_\_\_ Slot size \_\_\_\_\_ Set from \_\_\_\_\_ feet to \_\_\_\_\_ feet

Gravel packed? ☐ Yes ☒ No ☐ Size of gravel \_\_\_\_\_

Placed from \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface seal depth 18+ Material used in seal: ☐ Cement grout☒ Bentonite ☒ Puddling clay ☐ \_\_\_\_\_Sealing procedure used: ☐ Slurry pit ☐ Temp. surface casing☒ Overbore to seal depthMethod of joining casing: ☐ Threaded ☒ Welded ☐ Solvent


Weld

☐ Cemented between strata

Describe access port \_\_\_\_\_

## 6. LOCATION OF WELL

Sketch map location must agree with written description



Subdivision Name \_\_\_\_\_

Lot No. \_\_\_\_\_ Block No. \_\_\_\_\_

County BonnerSE  $\frac{1}{4}$  SW  $\frac{1}{4}$  Sec. 34, T. 58 N ☒ S ☐ R. 4 E ☐ W ☒

## 11. DRILLERS CERTIFICATION

I/We certify that all minimum well construction standards were  
complied with at the time the rig was removed.Firm Name Intermountain Firm No. 252Address Rt-1 Box 312 Date 12-18-91Signed by (Firm Official) Shannon D. Anglin

and

(Operator) Same