RECEIVED
JAN 2 6 1998
NORTHERN REGION IDWR

Form 238-7 3/96

IDAHO DEPARTMENT OF WATER RESOURCES
POSTED
WELL DRILLER'S REPORT
Use Typewriter or Ballpoint Pen

097442

Office Use Only
Inspected by TDK
Twp ___ Rge ___ Sec ___
___1/4 ___1/4 ___1/4
Lat: : : Long: : :

1. DRILLING PERMIT NO. R-00 3082
Other IDWR No. 97-97-N-35

2. OWNER:
Name Robert Ganzer
Address 2532 Pine Castle Dr.
City Hayford State Ca Zip 93230

3. LOCATION OF WELL by legal description:
Sketch map location must agree with written location.

N / W / E / S

Twp. 56 North ☒ or South ☐
Rge. 4 East ☐ or West ☒
Sec. 7 ___ 10 acres ___ 1/4 SW 40 acres 1/4 SE 160 acres 1/4
Gov't Lot ___ County Bonner
Lat: : : Long: : :
Address of Well Site East side Rd
Sandborn Rd City Priest River
(Give at least name of road + Distance to Road or Landmark)

Lt. ___ Blk. ___ Sub. Name ___

4. USE:
☒ Domestic ☐ Municipal ☐ Monitor ☐ Irrigation
☐ Thermal ☐ Injection ☐ Other ___

5. TYPE OF WORK check all that apply (Replacement etc.)
☒ New Well ☐ Modify ☐ Abandonment ☐ Other ___

6. DRILL METHOD
☐ Air Rotary ☒ Cable ☐ Mud Rotary ☐ Other ___

7. SEALING PROCEDURES

SEAL/FILTER PACK Material	From	To	AMOUNT Sacks or Pounds	METHOD
Bentonite	0	18	7	Temp Casing

Was drive shoe used? ☒ Y ☐ N Shoe Depth(s) ___
Was drive shoe seal tested? ☐ Y ☒ N How? ___

8. CASING/LINER:

Diameter	From	To	Gauge	Material	Casing	Liner	Welded	Threaded
6"	+1	142	250	Steel	☒	☐	☒	☐
					☐	☐	☐	☐
					☐	☐	☐	☐

Length of Headpipe ___ Length of Tailpipe ___

9. PERFORATIONS/SCREENS
☐ Perforations Method Telescoping
☒ Screens Screen Type Johnson

From	To	Slot Size	Number	Diameter	Material	Casing	Liner
142	147	60		6"	S.S.	☐	☐
						☐	☐
						☐	☐

138'

10. STATIC WATER LEVEL OR ARTESIAN PRESSURE:
~~150~~ ft. below ground Artesian pressure ___ lb.
Depth flow encountered ___ ft. Describe access port or control devices: ___

SWSE 7 56N 4W

11. WELL TESTS:
☒ Pump ☐ Bailer ☐ Air ☐ Flowing Artesian

Yield gal./min.	Drawdown	Pumping Level	Time
5	13	141	2 hrs

Water Temp. ___ Bottom hole temp. ___
Water Quality test or comments: ___
Depth first Water Encountered ___

12. LITHOLOGIC LOG: (Describe repairs or abandonment)

Bore Dia.	From	To	Remarks: Lithology, Water Quality & Temperature	Water Y	Water N
8	0	18	Top Soil Sand		X
6	18	30	Sand Gravel		X
	30	70	Sand med.		X
	70	100	Sand fine + med.		X
	100	130	Sand fine		X
	130	147	Sand fine	X	
	147	150	Clay + Sand	X	

Completed Depth 147' (Measurable)
Date: Started 8-25-97 Completed 9-5-97

13. DRILLER'S CERTIFICATION
I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Firm Name Carl Pitts & Sons Drilling Firm No. 168
Firm Official Carl Pitts Date 9-8-97
and
Supervisor or Operator Steve Pitts Date 9-8-97
(Sign once if Firm Official & Operator)