

STATE OF IDAHO
DEPARTMENT OF WATER RESOURCES
WELL DRILLER'S REPORTState law requires that this report be filed with the Director, Department of Water Resources
within 30 days after the completion or abandonment of the well.RECEIVED
JULY 24 1988
OCT 24 1988
TYPEWRITER OR
BALLPOINT PEN

1. WELL OWNER		7. WATER LEVEL	
Name <u>HIGBY RANCH (Pat)</u>		Static water level <u>95</u> feet below land surface.	
Address <u>FORT WILSON DRIVE</u>		Flowing? ☐ Yes ☒ No G.P.M. flow _____	
Owner's Permit No. <u>Payette Ida</u>		Artesian closed-in pressure _____ p.s.i.	
		Controlled by: ☐ Valve ☐ Cap ☐ Plug	
		Temperature <u>68</u> °F. Quality _____	
		Describe artesian or temperature zones below _____	
2. NATURE OF WORK <u>65-7462</u> <u>65-89-2-02</u>		8. WELL TEST DATA	
☒ New well ☐ Deepened ☐ Replacement		☒ Pump ☐ Bailer ☐ Air ☐ Other _____	
☐ Abandoned (describe abandonment procedures such as materials, plug depths, etc. in lithologic log)		Discharge G.P.M. <u>40</u> Pumping Level <u>130</u> Hours Pumped <u>48 hours</u>	
3. PROPOSED USE		9. LITHOLOGIC LOG <u>072781</u>	
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal		Bore Diam. Depth From To Material Water Yes No	
☐ Industrial ☒ Stock ☐ Waste Disposal or Injection		10 0 12 SILTY SAND	
☐ Other _____ (specify type)		10 12 18 CEMENTED GRAVEL	
4. METHOD DRILLED		10 18 24 SILTY SAND	
☒ Rotary ☒ Air ☐ Hydraulic ☐ Reverse rotary		10 24 32 CEMENTED GRAVEL	
☐ Cable ☐ Dug ☐ Other _____		10 32 50 SILTY CLAY	
5. WELL CONSTRUCTION		6 50 95 SILTY BROWN CLAY	
Casing schedule: ☒ Steel ☐ Concrete ☐ Other _____		6 95 117 BLUE CLAY	
Thickness Diameter From To		6 117 118 COARSE SAND X	
<u>.250</u> inches <u>6</u> inches + <u>1</u> feet <u>122</u> feet		6 118 158 BLUE CLAY	
<u>.258</u> inches <u>5</u> inches <u>2</u> feet <u>260</u> feet		6 158 168 SAND X	
_____ inches _____ inches _____ feet _____ feet		6 168 172 BLUE CLAY	
_____ inches _____ inches _____ feet _____ feet		6 172 173 FINE SAND GREY X	
Was casing drive shoe used? ☒ Yes ☐ No		6 173 180 BLUE CLAY	
Was a packer or seal used? ☐ Yes ☒ No		6 180 181 FINE GREY X	
Perforated? ☒ Yes ☐ No		6 181 202 BLUE CLAY	
How perforated? ☐ Factory ☐ Knife ☒ Torch		6 202 203 FINE GREY X	
Size of perforation <u>1/8</u> inches by <u>6</u> inches		6 203 208 BLUE CLAY	
Number From To		6 208 209 FINE GREY SAND X	
<u>60</u> perforations <u>115</u> feet <u>121</u> feet		6 209 217 BLUE CLAY	
_____ perforations _____ feet _____ feet		6 217 218 FINE GREY SAND X	
_____ perforations _____ feet _____ feet		6 218 230 BLUE CLAY	
Well screen installed? ☒ Yes ☐ No		6 230 233 FINE GREY SAND X	
Manufacturer's name <u>COOK</u>		6 233 260 BLUE CLAY	
Type <u>304 STAINLESS</u> Model No. _____		***NOTR***	
Diameter <u>5</u> Slot size <u>20</u> Set from <u>234</u> feet to <u>229</u> feet		FIVE SEPARATE SCREEN SECTIONS	
Diameter <u>5</u> Slot size <u>20</u> Set from <u>208</u> feet to <u>203</u> feet		5' screen 20 slot 182-177	
Gravel packed? ☒ Yes ☐ No ☐ Size of gravel <u>9-14</u> Sand		5' screen 20 slot 166-161	
Placed from <u>0</u> feet to <u>260</u> feet		5' screen 20 slot 121-116	
Surface seal depth <u>60</u> Material used in seal: ☐ Cement grout			
☒ Bentonite ☐ Pudding clay ☐ _____			
Sealing procedure used: ☐ Slurry pit ☐ Temp. surface casing			
☒ Overbore to seal depth			
Method of joining casing: ☐ Threaded ☒ Welded ☐ Solvent Weld			
☐ Cemented between strata			
Describe access port _____			
6. LOCATION OF WELL		10. Work started <u>2/18/88</u> finished <u>2/25/88</u>	
Sketch map location must agree with written location		11. DRILLERS CERTIFICATION	
Subdivision Name <u>Payette</u>		I/We certify that all minimum well construction standards were complied with at the time the rig was removed.	
Lgt No. _____ Block No. _____		DALLAS DRILLING & PUMP CO., INC. Firm No. <u>445</u>	
County <u>NE 1/4 SE 1/4 Sec. 17, T. 3N, R. 4W E.W.</u>		505 SOUTH 18TH STREET #145 Date <u>3/23/88</u>	
		PAYETTE, IDAHO Signed by (Firm Official) <u>John J. Bell</u>	
		and (Operator) <u>John J. Bell</u>	

Department of Water Resources

USE ADDITIONAL SHEETS IF NECESSARY — FORWARD THE WHITE COPY TO THE DEPARTMENT





0006002714

**STATE OF IDAHO***Office of the secretary of state, Phil McGrane***ANNUAL REPORT**

Idaho Secretary of State

PO Box 83720

Boise, ID 83720-0080

(208) 334-2301

Filing Fee: \$0.00

*For Office Use Only***-FILED-**

File #: 0006002714

Date Filed: 12/3/2024 12:41:11 PM

B0967-8720 12/03/2024 12:41 PM Received by Office of the Idaho Secretary of State

Entity Name and Mailing Address:

Entity Name:

BIR FEEDLOT LLC

The file number of this entity on the records of the Idaho

0000119750

Secretary of State is:

Address

3990 HIGHWAY 52
PAYETTE, ID 83661-5131

Entity Details:

Entity Status

Active-Existing

This entity is organized under the laws of:

IDAHO

If applicable, the old file number of this entity on the records of
the Idaho Secretary of State was:

W35709

The registered agent on record is:

Registered Agent

GEORGE E COLWELL

Registered Agent

Physical Address

3990 HIGHWAY 52
PAYETTE, ID 83661

Mailing Address

83661

Limited Liability Company Managers and Members

Name	Title	Business Address
GEORGE E COLWELL	Manager	3990 HIGHWAY 52 PAYETTE, ID 83661

The annual report must be signed by an authorized signer of the entity.

Job Title: Manager

George E. Colwell

Sign Here

12/03/2024

Date

HIGBY $\frac{N}{N}$ RANCH

• Fine Commercial Cattle •
PAYETTE, IDAHO 83881

STAR ROUTE

PHONE 208-642-2525

5a, & 7a.

CFS

Purpose

Dates Used

Pump & Motor

Casing

Depth

— 1. .059 Stock 1-1 to 12-31 3Hp 1 HP Sub. 8" 210

— 2 .078 Stock 1-1 to 12-31 1 1/2 Hp 1 HP Sub. 8" 110

— 3 .294 Stock 1-1 to 12-31 * 1 HP Sub 8" 46

— 4 .294 Stock 1-1 to 12-31 1 1/2 Hp 1 HP Sub 40GPM 8" 120

5. .392 Stock 1-1 to 12-31 1 Hp 1 HP Sub. 8" 180

6. .049 Dom/Stock 1-1 to 12-31 * 3/4 HP Sub 6" 60'

Gravity flow from system vault ^{cement}
stock - 2500 bf 50' x 15' x 10'

1" line → system → 6" line
to feedlot, gradually reduced
to 1"

sec 17 NESE \ 4 wells feed system then
Gov 4 SWSE / 35 tanks (6 x 4 x 2) 375 gal

NWSE - 1 house, 10 bf ^{3/4 HP starite}
#C48KZP100

⁴⁵
²¹
⁴²
20 SW NW - 1 house, 40 bf ^{550XHAB-3901}
SW NE - 1 trailer, 40 bf ^{vacuum jet}
1" line

11.62

1216.2